



SPI Host-Controller Interface

Bluetooth Applications Group

ABSTRACT

This document describes the Serial Peripheral Interface (SPI™) Host-Controller interface (HCI) for the BRF63xx from Texas Instruments. Specifically, it discusses the following information:

- Supported features
- Shared SPI bus mode

Contents

1	Overview	2
2	Supported BTSPI Features.....	2
3	BRF63xx Pinouts for HCI Transport Layer	2
4	BTSPI Interface Description.....	2
5	BTSPI Transactions	4
6	Clock Polarity.....	7
7	Shared SPI Bus Mode	8
8	Initialization Commands for BTSPI	9
9	Related Commands.....	10
10	References.....	10
Appendix A	Sample Commands Hex Dump	11
Appendix B	Timing Information	12

List of Figures

1	SPI Interface Signals.....	2
2	BTSPI Write Transaction	4
3	BTSPI Read Transaction	6
4	Shared SPI Bus Topology.....	8
B-1	BTSPI Write Timing.....	12
B-2	BTSPI Read Timing.....	12

List of Tables

1	Transport Layer Pinout Multiplexing	2
2	SPI Interface Signals Description	3
3	BT SPI Read/Write Transaction—16-bit Alignment	5
4	Reference Documents.....	10
B-1	BTSPI Read/Write Timing.....	12

Bluetooth is a registered trademark of Bluetooth SIG.
 SPI is a trademark of Motorola, Inc.
 All other trademarks are the property of their respective owners.

1 Overview

The BRF63xx provides a TI Bluetooth® SPI (BTSPI) transport layer, in addition to the universal asynchronous receiver/transmitter (UART) and the secure digital input/output (SDIO) interfaces. The SPI interface provides high-speed data transfer capability with low power consumption for mobile electronic devices. The SPI bus is used as interface between a host and several different TI devices (including WLAN, Bluetooth and DTV). The SPI bus was designed to operate on a point-to-multipoint basis by providing a separate, active-low chip select (\overline{CS}) per device.

2 Supported BTSPI Features

BTSPI supports the following features:

- Incorporates a deep-sleep protocol
- Transport layer H4
- Point-to-multipoint
- Supports Bluetooth (BT) basic, EDR2 and EDR3 data rates
- Maximum supported clock rate = 13MHz
- BRF63xx is always SPI Slave, host is always SPI Master

3 BRF63xx Pinouts for HCI Transport Layer

The BRF63xx supports three transport layers that are multiplexed on the same I/O pins listed in [Table 1](#).

Table 1. Transport Layer Pinout Multiplexing⁽¹⁾

	UART	SDIO (1-bit)	SPI
CLK (I)	—	CLK (I)	CLK (I)
RX (B)	RX (PU, I)	CMD (B)	DI (I)
CTS (I)	CTS (PU, I)	IRQ (O)	\overline{CS} (PU, I)
RTS (B)	RTS (PU, O)	IRQ (O)	IRQ (O)
TX (B)	TX (PU, O)	DATA (B)	DO (O)

⁽¹⁾ **Key:** I = Input; O = Output; PU = ???; B = ???

4 BTSPI Interface Description

In order to facilitate a broad implementation, the protocol is half duplex and does not require simultaneous operation of data OUT (DO) and data IN (DI). All TI communication devices are slaves in this protocol, and all transactions are initiated by the host, as SPI Master. The clock rate for each one of the connected devices may be different and configured per device.

[Figure 1](#) illustrates the SPI interface signals; [Table 2](#) describes the SPI interface signals.




Figure 1. SPI Interface Signals

Table 2. SPI Interface Signals Description

Port Name	I/O	Description
BTSPi_CLK	I	Clock (0MHz to 13MHz) from host to slave
BTSPi_DI	I	Data from host to slave
BTSPi_CS	I	\overline{CS} signal from host to slave
BTSPi_IRQ	O	Interrupt from slave to host
BTSPi_DO	O	Data from slave to host

During reset, all outputs are in high-impedance mode and all pull-up resistors are pulled up.

4.1 \overline{CS} and Bus Sharing Operation

The \overline{CS} line selects a specific device on the shared SPI bus. \overline{CS} is asserted at the beginning of an SPI transaction and de-asserted when the transaction completes; \overline{CS} must not be de-asserted during the transaction.

Bus sharing by multiple devices is implemented by asserting one \overline{CS} signal at a time and performing transactions with a specific device. Device multiplexing is performed on a transaction basis rather than on a byte or word basis.

4.2 Sleep Protocol

In order to optimize power consumption, the BRF63xx device toggles between an active state and a low-power mode (deep sleep).

When operating in low power mode, the device deactivates most of its logic and is not capable of full-speed transactions with the host. The host must wake up the device when the BRF63xx is in sleep mode.

The wake-up protocol is based on assertion of \overline{CS} . The BT device performs its wake-up procedure and responds by asserting the IRQ line. \overline{CS} must be asserted for a minimum time of 31 μ s in order for a BRF63xx device in sleep mode to recognize the signal.

Note: If a BRF63xx device is in sleep mode, any transactions (read or write) should not be started until the IRQ line is asserted.

The SPI driver within the host does not have to be aware of the sleep state of the device. It is the responsibility of the BT stack to report to the SPI driver what state the device is in.

This procedure is also utilized as a method for flow control. The BT stack always signals the SPI driver that the device is in sleep mode. In response to a \overline{CS} assertion, the BRF63xx device asserts the IRQ line only when it has enough free buffer space to receive a transaction.

Note: The delay from \overline{CS} assertion to the IRQ line assertion may vary, depending on the actual state of the BRF63xx device and the delay in system clock activation. The delay does not exceed 2ms under worst-case conditions in order to prevent bus blocking. In normal operation, the delay until IRQ line assertion is significantly shorter, and polling of the IRQ line may be beneficial.

BTSPI Transactions

4.2.1 Enabling the BTSPI Deep Sleep Protocol

Deep Sleep operation is disabled at power-up by default. In order to enable the BRF Deep Sleep feature and make the Deep Sleep protocol active, the host must first send an

HCI_VS_Sleep_Mode_Configurations command:

```
Send_HCI_VS_Sleep_Mode_Configurations 0xFD0C, 1, 1, 0x06, 0xFF, 0xFF, 0xFF, 0, 100
Wait_HCI_Command_Complete_VS_Sleep_Mode_Configurations_Event 5000, any,
HCI_VS_Sleep_Mode_Configurations, 0x00
```

Refer to [Section 9](#) for a detailed description of this command.

5 BTSPI Transactions

Note: The first command to be sent to the BRF63xx requires special consideration. Refer to [Section 8](#) for more details.


5.1 Write/Read Transactions

5.1.1 16-Bit Alignment

All data sent or received over the BT SPI interface are 16-bit aligned.

5.1.2 Write Operation—Host to BRF63xx Data Transfer

[Figure 2](#) shows the BTSPI write transaction timing.



(1) Padding byte for 16-bit alignment, if required.

Figure 2. BTSPI Write Transaction

SPI Header:

MOSI	=	BRF63xx Data In
MISO	=	BRF63xx Data Out
Write	=	Opcode for write is 0x01
M _{MSB} , M _{LSB}	=	16-bit data payload length (including alignment byte)
Busy	=	Busy byte (0x00)

SPI Payload (equal to the HCI command + padding byte):

D0 ...Dn = 0x00 (depending of number of bytes in SPI payload)
XX = Should be ignored by master

In order for the total SPI packet (that is, the SPI transaction) to be 16-bit aligned, the HCI command must be padded with an additional 0x00 byte if the HCI packet is even size. Refer to [Table 3](#) for more information.

Table 3. BT SPI Read/Write Transaction—16-bit Alignment

SPI Header	SPI Payload (HCI Command)	Padding Byte
5 bytes	Odd	None
5 bytes	Even	0x00

The host must assert \overline{CS} (that is, drive the signal to low) before sending data on the DI line.

After completing its wake-up sequence, the BT device asserts the IRQ line to inform the host that it is ready.⁽¹⁾

If the Bluetooth device is awake, the IRQ line is asserted immediately (within ≤ 250 ns). When the BT device detects the HCI packet header, it de-asserts its IRQ line. When the host completes the SPI transaction, it must de-assert its \overline{CS} line.

Note: The host can wake up the Bluetooth device by generating a pulse on the \overline{CS} line or performing a write transaction.

The write transaction is performed according to the following parameters:


- A complete HCI packet must be included within every SPI transaction. However, the HCI header and HCI payload may be sent in different SPI transactions.
- The number of bytes for each SPI transaction will always be even.
- The padding byte is added at the end of the HCI packet, but is not reflected in the HCI header length parameter (H4 packet length ignores this byte).
- The BRF63xx will ignore the additional byte.

⁽¹⁾ The wake-up sequence period depends on whether or not the external fast clock is available; the external fast clock is configurable by the HCI_VS_Fast_Clock_Configuration command. Refer to the *BRF6350 HCI Vendor-Specific Command* document ([SWRU115](#)).

BTSPI Transactions

5.1.3 Read Operation—BRF63xx to Host Data Transfer

Figure 3 shows the BTSPI read transaction timing.



(1) Padding byte for 16-bit alignment, if required.

Figure 3. BTSPI Read Transaction

SPI Header:

Read	=	Opcode for write is 0x03
S_{MSB} , S_{LSB}	=	16-bit data payload length (including alignment byte)
Busy	=	Busy byte (0x00)

SPI Payload (equal to the HCI command + padding byte):

$D(0) \dots D(n)$	=	0x00 (depending of number of bytes in SPI payload)
-------------------	---	--

In order for the total SPI packet (that is, the SPI transaction) to be 16-bit aligned, the HCI event sent from the BT device is padded with an additional 0x00 byte (if required). Refer to [Table 3](#) for more information.

The BT device signals to the host its desire to transfer data by asserting the IRQ line. The host asserts \overline{CS} and performs a read transaction. Upon completing the read transaction, the host must de-assert \overline{CS} . The Bluetooth device then de-asserts its IRQ line immediately as a response (within $\leq 250\text{ns}$).

Note: The host should be set to trigger on high to low edge.

The read transaction is performed according to the following parameters:

- A single BTSPI read transaction includes a full HCI packet.
- The number of bytes for each SPI transaction will always be even.
- The padded byte is added at the end of the HCI packet, but is not reflected in the HCI header length parameter (H4 packet length ignores this byte).
- The host should read a full SPI packet (including the alignment byte) according to the SPI packet length (S_{MSB} and S_{LSB}).
- **The host must ignore the additional byte according to the HCI packet length.**

Refer to [Appendix B](#) for the BTSPI read and write timing diagrams.

6 Clock Polarity

The polarity of the clock used by the SPI protocol can be switched by initiating a vendor-specific command, **HCI_VS_TI_SPI_Configuration**, through the SPI interface (refer to [Appendix A](#) for a detailed description of this command).

The switching command must be sent using the default clock polarity as described in [Figure B-1](#) and [Figure B-2](#), but the polarity can be switched for subsequent transactions..

7 Shared SPI Bus Mode

This section describes the TI solution for a system in which the SPI host controller interfaces with both Bluetooth (BRF63xx) and WLAN (WL1251) devices.

The topology includes one SPI master and an SPI bus shared by several slaves. The bus topology has a single master (Host) and multiple slaves (WLAN and Bluetooth devices). The following lines are common to all SPI devices in the system:

- CLK
- Data IN
- Data OUT—when this line is shared between the different devices, it must be set to tri-state when \overline{CS} is de-asserted via the vendor-specific command, **HCI_VS_TI_SPI_Configuration** (refer to [Section 9](#))

[Figure 4](#) illustrates the shared SPI bus architecture.




Figure 4. Shared SPI Bus Topology

8 Initialization Commands for BTSPI

In order for the BRF63xx to operate using BTSPI protocol, the following commands must be sent to the device. These commands must be sent in the specified order:

1. When working in non-shared mode:

```
Send_HCI_VS_TI_SPI_Configuration 0xFD41, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0
Wait_HCI_Command_Complete_VS_TI_SPI_Configuration_Event 5000, any,
HCI_VS_TI_SPI_Configuration, 0x00
```

When working in shared mode:

```
Send_HCI_VS_TI_SPI_Configuration 0xFD41, 0, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0
Wait_HCI_Command_Complete_VS_TI_SPI_Configuration_Event 5000, any,
HCI_VS_TI_SPI_Configuration, 0x00
```

Whether working in shared or non-shared mode, this command must be the first command sent to the BRF63xx (even before the initialization script). Refer to [Appendix A](#) for a HEX dump example of this command.

CAUTION

The normal SPI host write sequence is \overline{CS} low (host → BRF63xx device), followed by IRQ low (BRF63xx device → host), indicating that the BRF63xx device is ready to accept data. However, after power-up, IRQ goes low automatically to indicate that device power up is complete—it is the same line as RTS.

Therefore, for the first command only, the host cannot rely on the IRQ line going low. The host must wait for a delay of more than 50μs before sending the SPI packet.

In addition, during this command the BRF63xx device performs its internal processing to switch to the required SPI mode. This processing requires an additional small amount of time. Therefore, for the first command only, a short delay is required after the first four bytes and before the following 21 bytes. This delay must also be greater than 50μs.

2. Enabling the deep-sleep protocol:

```
Send_HCI_VS_Sleep_Mode_Configurations 0xFD0C, 1, 1, 0x06, 0xFF, 0xFF, 0xFF, 0, 100
Wait_HCI_Command_Complete_VS_Sleep_Mode_Configurations_Event 5000, any,
HCI_VS_Sleep_Mode_Configurations, 0x00
```

3. All the commands of the most recent initialization script

4. Other platform-related commands

Related Commands

9 Related Commands

The following vendor-specific commands are used for SPI mode. For additional details, refer to the application notes *BRF6350 HCI Vendor-Specific Command* ([SWRU115](#)) and *BRF6300 Vendor-Specific Commands* (BT-SW-0030).

- HCI_VS_Sleep_Mode_Configurations
- HCI_VS_TI_SPI_Configuration

10 References

[Table 4](#) lists some of the reference documents that are recommended to the user for additional information.

Table 4. Reference Documents

Document	Reference
BRF63xx Product Review Rev 0.41	BT-DS-0023
BRF6300 Vendor-Specific Commands	BT-SW-0030
BRF6350 Vendor-Specific Commands	SWRU115

Appendix A Sample Commands Hex Dump

HCI_VS_TI_SPI_Configuration Command (non-shared mode):

01 00 **15 00 00** 01 41 fd 11 00 01 00 00 00 01 00 00 00 00 00 00 00 00 00 00

The first five bytes (in **bold**) are the SPI header. The last 21 bytes are the HCI_VS_SPI_Configuration command bytes.

Command Complete for VS TI SPI:

03 00 00 00 09 00 0E 04 01 05 FD 41 00

Read BD address:

01 00 05 00 00 00 09 01 00 10

Command Complete of read BD address:

03 00 00 00 0f 00 0E 04 01 0A 10 09 61 00 69 67 47 69 97 -

Write Scan Enable:

01 00 07 00 00 00 1A 01 01 0C 03 00

Command Complete Event for write scan enable:

03 00 00 00 09 00 0E 04 01 04 0c 1A 00

Read Scan Enable:

01 00 05 00 00 00 19 01 00 0C

Command Complete for Read Scan Enable:

03 00 00 00 09 00 0E 04 01 05 0c 19 03 00

Max slots 5 event:

03 00 00 00 07 00 1b 04 01 03 05 00

Appendix B Timing Information

Figure B-1 and Figure B-2 show the BTSPI write and read timing sequence, respectively. Table B-1 defines the BTSPI read/write timing parameters.




Figure B-1. BTSPI Write Timing




Figure B-2. BTSPI Read Timing

Table B-1. BTSPI Read/Write Timing

Time	Result (Typ)
t_1	142ns
t_2	11ns
t_3	1170ns
t_4	135ns

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
Low Power Wireless	www.ti.com/lpw

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2007, Texas Instruments Incorporated

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
Low Power Wireless	www.ti.com/lpw

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265