



Technical Documentation

ANR 2.X - OVERVIEW

Document Number:	L1D_AS110
TI Department	European Wireless Terminal Chipset Business Unit
Version:	2.3
Status:	APPROVED
Date:	January 17, 2005

IMPORTANT NOTICE

Texas Instruments Incorporated and / or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and / or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and / or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and / or copied subject to and strictly in accordance with all the terms of such license agreements.

Customers acknowledge and agree that TI products and / or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and / or the licensing of software do not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

Date of change	Changed by	Approved by	Date of approval	Version	Notes
April-25-2003	Thierry Le Gall	Gilles Dassot		0.1	(1)
June-15-2004	Sebastien Guiriec	Sebastien Guiriec		1.0	(2)
June 23, 2004	Thierry Le Gall			1.1	(3)
January 17 2005	Fabien Ober	Thierry Le Gall	04 Feb 2005	2.0	(4)
July 26, 2005	Thierry Le Gall			2.1	(5)
				2.2	(6)
September 30, 2005	Saurabh Gupta	Sebastien Guiriec	September 30, 2005	2.3	(7)

Notes

- (1) Creation.
- (2) Update version number to 1.0.
- (3) Change field status of the document.
- (4) Added ANR 2.1.
- (5) Updates.
- (6) Changes done in 2.2 not updated in absence of change info.
- (7) Inserted Fields in the File properties and header so that it's updated automatically. History table updated version 1.2 renamed to 2.0, 1.3 renamed to 2.1.

Table of Contents

ANR 2.x - Overview	1
1 Introduction	5
2 The Ambient Noise Problem	5
3 The ANR Signal Processing Strategy	5
3.1 ANR 2.0 Signal Processing Strategy	5
3.2 The ANR 2.1 Signal Processing Strategy	6
Appendices	7
A. Acronyms	7
B. Glossary	7

List of Figures and Tables

FIGURE 3-1 THE ANR 2.0 BLOCK DIAGRAM	5
FIGURE 3-2 THE ANR 2.1 BLOCK DIAGRAM	6

List of References

- [1] [L1D_AS118-1, TRD for the Ambient Noise Reduction – ANR 2.x](#)
- [2] [L1D_AS111-1 – ANR 2.0 – API Definition](#)
- [3] [L1D_AS111-2 – ANR 2.1 – API Definition](#)

1 Introduction

This document is an overview about the Ambient Noise Reduction (ANR) algorithm. This document applies to ANR 2.0 and next upgrades ANR 2.x. A first part presents the ANR problem generally speaking, its issues and its rules in the GSM audio processing chain. A second part is dedicated to the ANR 2.0 [2] and ANR 2.13 [3] signal processing constraints, the algorithm strategy adopted its main advantages.

2 The Ambient Noise Problem

Audio quality is still one of the most important parameter that the end-user evaluates in a mobile phone. It is then very important to provide audio algorithm which can improve this quality.

When the mobile phone operates in a noisy acoustic environment or when cheap components are used that generate internal noise, the speech intelligibility is damaged and the conversation between the far end and the near end speakers becomes unpleasant. In addition, a low Signal to Noise Ratio (SNR) context is unfavorable to the vocoder and speech recognition tasks and thus degrades the overall performances of the handset.

In the aim to increase the SNR, an ambient noise reduction signal processing algorithm is necessary to remove the undesirable noise part of the handset downlink signal as much as of the terminal uplink signal.

3 The ANR Signal Processing Strategy

Several constraints are rising on the choice of the ANR algorithm [1]. First, noise rejection must be completed on the downlink and the uplink noise corrupted signal without introducing any undesirable artifacts or speech distortion. Second, due to the mobile phone context, not any noise reference signal is available because only one microphone is used on each side of the communication. Third, the real time constraints and the limited power computation and consumption inherent in the embedded digital signal processor of the mobile phone imply to resort to low complexity algorithms.

3.1 ANR 2.0 Signal Processing Strategy

In consideration of the aforementioned constraints, the signal processing strategy adopted to implement the ANR 2.0 module rely on a Time Domain Attenuation (TDA) acting in synergy with a spectral subtraction technique.

The functional scheme is the following: the ANR 2.0 input signal frames are computed in the frequency domain using the Fast Fourier Transform (FFT) algorithm. The corresponding spectrum frames are subtracted with the last estimated noise spectrum frames. The subtraction result is transformed in the time domain using the inverse FFT (iFFT) algorithm which delivers the ANR output signal. The last signal processing step is achieved with the TDA which attenuates the out coming signal using a variable gain depending on the VAD decisions (Figure 3-1).




Figure 3-1 The ANR 2.0 Block Diagram

Such a signal processing strategy presents the advantages to remove the noise during the speech occurrences in the corrupted signal with few distortions and without the need of a noise reference signal. Thus far, the implemented algorithms have a reasonable overall complexity.

The main drawback of the TDA coupled with the spectral subtraction technique is the need for a Voice Activity Detector (VAD) which increases the algorithm complexity. The VAD rule consists in discerning between the speech frames and the noise frames for the noise estimation (NES) and for the TDA gain controlling. Consequently, the ANR performances are in a great dependency with the VAD decision errors.

In the ANR 2.0, the use of a TDA driven by the VAD decisions lead to sudden attenuation application on the signal. This generates audible noise and speech fluctuation. In low SNR situation, this can be very annoying.

Secondly, the ANR 2.0 reveals to be sensitive to some Full-Type Agreement (FTA) tests signal preventing to pass successfully the releases 99 and 4 sending distortion test.

To correct these two issues, the ANR 2.0 was upgraded to ANR 2.1.

3.2 The ANR 2.1 Signal Processing Strategy

In the ANR 2.1, the TDA has been removed and the internal frequency domain VAD has been replaced by an external time-domain VAD 1.x. In addition, a tone detector has been added. Its aim is to detect pure test tones and to let them pass through the ANR 2.1 for FTA tests. This gives the functional scheme as presented below (Figure 3-2).




Figure 3-2 The ANR 2.1 Block Diagram

The TDA will no more leads to strong non-linear artifact.

Appendices

A. Acronyms

ANR	Ambient Noise Rejection / Reduction
GSM	Global System for Mobile
SNR	Signal to Noise Ratio
FFT	Fast Fourier Transform
iFFT	Inverse Fast Fourier Transform
VAD	Voice Activity Detector / Detection
NES	Noise Estimator / Estimation
TDA	Time Domain Attenuation
FTA	Full Type Agreement

B. Glossary