



Technical Documentation

ECHO SUPPRESSOR - OVERVIEW

Document Number:	L1D_AS260
TI Department	European Wireless Terminal Chipset Business Unit
Version:	1.3
Status:	APPROVED
Date:	June 22, 2004

IMPORTANT NOTICE

Texas Instruments Incorporated and / or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and / or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and / or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and / or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and / or software may be based on or implements industry recognized standards and that certain third party may claim intellectual property rights therein. The supply of products and / or the licensing of software do not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of TI.

History

Date of change	Changed by	Approved by	Date of approval	Version	Notes
March 18, 2004	Alan McCree, Takahiro Unno, Thierry Le Gall	Sébastien Guiriec		0.1	(1)
March 18, 2004	Thierry Le Gall	Sébastien Guiriec	March 18, 2004	1.0	(2)
June 22, 2004	Thierry Le Gall			1.1	(3)
March 17, 2005	Sébastien Guiriec	Sébastien Guiriec	March 17, 2005	1.2	(4)
September 30, 2005	Saurabh Gupta	Sébastien Guiriec	September 30, 2005	1.3	(5)

Notes

- (1) Creation.
- (2) Approval.
- (3) Minor change: updated document status field.
- (4) Update reference table
- (5) Removed track changes

Glossary

ES	Echo Suppressor/Suppression
AEC	Acoustic Echo Canceller/Cancellation
TCS	TI's Chipset Solution
DL	Downlink
UL	Uplink
VAD	Voice Activity Detector/Detection
TCL	Terminal Coupling Loss
NSF/NFA	Noise Floor Adjustment
ALS	Attenuation Level Smoothing
CNG	Comfort Noise Generator

References

- [1] L1D_AS088 – Audio Enhancement SW PRD
- [2] ITU-T Recommendation P340, "Transmission Characteristics and Speech Quality Parameters of Hands-free Terminals", May 2000.

Table of Contents

1	Introduction	5
2	Echo Suppressor Role	5
3	Echo Suppressor Description	5
3.1	Embedded Voice Activity Detector	5
3.2	Terminal Coupling Loss Estimator	6
3.3	Echo Suppressor Control Algorithm	6
3.4	Comfort Noise Generator	6
4	Conclusion	6

List of Figures and Tables

Figure 2.1	The Conventional AEC/ES Block Diagram	5
------------	---	---

1 Introduction

This document provides an overview of the Echo Suppressor (ES) module implemented beside the Acoustic Echo Canceller (AEC) for the TCS3.1 delivery and further [1]. A first chapter deals with the ES role beside the AEC. A second chapter is dedicated to a top level description of the ES module.

2 Echo Suppressor Role

The ES role is to control the residual echo in a speakerphone application, where the AEC is unable to cancel the entire echo in the uplink due to non-ideal acoustical environment such as a non-linear loudspeaker response for example (Figure 2.1).




Figure 2.1 The Conventional AEC/ES Block Diagram

The primary goal is to achieve significant attenuation to S_{out} when only the far-end speaker is talking, to reduce residual echo, with no attenuation or distortion of S_{out} during near-end speech only. In double-talk situations, both paths are attenuated to control echo while still allowing both speakers to be heard. In idle, both signals can be passed through to preserve background noise characteristics, or S_{out} can be attenuated to reduce idle noise.

3 Echo Suppressor Description

The ES implemented in the TCS3.x delivery is acting both in the DL and in the UL. The ES processing is based on 20ms frame duration. The ES can be configured to provide various degrees of full, partial or half-duplex communication modes. The ES can be seen as a system made up of a downlink and an uplink Voice Activity Detector (VAD), a Terminal Coupling Loss (TCL) estimator, a Control Algorithm and a Comfort Noise Generator (CNG).

3.1 Embedded Voice Activity Detector

The embedded voice activity detectors act both in the DL and in the UL to provide information to the ES control algorithm. The VADs decisions are based on frame and noise energy estimations of the current 20ms frames compared to predefined thresholds. The VAD algorithm is the same DL and UL.

3.2 Terminal Coupling Loss Estimator

In addition to the VADs decisions, the ES uses the TCL estimation. TCL is estimated with downlink signal $s(n)$ and AEC output $e(n)$.

3.3 Echo Suppressor Control Algorithm

From the VADs decisions and from the TCL estimation, the ES control algorithm performs the states estimation on the current frame. The ES gain computation is based on four states: Idle, Double-Talk, Far-end and Near-end.

In each state, there is a desired attenuation level for both directions: receive out (R_{out}) and send out (S_{out}) depending on the selected communication mode: full-duplex, partial-duplex or half-duplex as specified in the ITU recommendation [2](Chap. 8).

The ES control algorithm can involve some optional options to improve the subjective audio quality: NSF/NFA (Noise Floor Adjustment) in UL and Attenuation Level Smoothing (ALS) independently in UL and in DL.

The NSF/NFA option allows the ES attenuation to be lowered by the estimated noise level and so reduces the noise frames chopping in the UL. The ALS option leads to DL and UL gains smoothing and so reduces the fast variations of the speech level in the ES outputs.

3.4 Comfort Noise Generator

The Comfort Noise Generation (CNG) acting in UL is another optional feature of the ES. The CNG can be activated as an alternative option to the NSF/NFA. The CNG adds random noise in the ES output and so masks the noise frames chopping in the UL.

4 Conclusion

The echo suppressor implemented in the TCS3.x solutions is based on voice activity detection in downlink and in uplink, terminal coupling loss and states estimation. The computation is based on 20ms frames. The ES modules can be configured either of full-duplex, partial-duplex or half-duplex communication mode. Embedded optional features can be activated to improve the subjective audio quality in the outputs.