



Technical Documentation

SixTies % CSSN. Low Level Design specification.

Department:	WTBU - Cellular Systems		
Creation Date:	2004-08-18		
Last Modified:	2004-08-18 by JuanVi Jativa-Villoldo		
ID:	8462.737.04	Version:	001
Status:	Submitted	ECCN:	Not Applicable

© 2004 Texas Instruments Incorporated. All rights reserved.

Texas Instruments Proprietary Information

Internal Data

0 Document Control

© 2004 Texas Instruments Incorporated. All rights reserved.

Texas Instruments Incorporated and / or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and / or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and / or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and / or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and / or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and / or the licensing of software do not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of TI.

0.1 Export Control Statement

Recipient agrees that it will not knowingly export or re-export, directly or indirectly, any product or technical data (as defined by the U.S, EU and other Export Administration Regulations) including software, or any controlled product restricted by other applicable national regulations, received from Disclosing party under this Agreement, or any direct product of such technology, to any destination to which such export or re-export is restricted or prohibited by U.S or other applicable laws, without obtaining prior authorization from U.S. Department of Commerce and other competent Government authorities to the extent required by those laws. This provision shall survive termination or expiration of this Agreement.

According to our best knowledge of the state and end-use of this product or technology, and in compliance with the export control regulations of dual-use goods in force in the origin and exporting countries, this

technology is classified as given on the front page.

This product or technology may require export or re-export license for shipping it in compliance with certain countries regulations.

0.2 Document History

Date	Version	Status	Author
2004-08-18	001	Draft	JuanVi Jativa-Villoldo
Initial version.			

0.3 References, Abbreviations, Terms

Table of Contents

1	Introduction.....	5
2	Interface changes.	7
2.1	Supplementary service notifications %CSSN.....	7
3	Proposed Low Level Design.	8
3.1	Interface Changes	8
3.2	ATI Modifications.	8
3.2.1	New Functions:.....	8
3.2.2	Modified Functions:.....	8
3.2.3	Affected Global variables:.....	8
3.2.4	Description of the changes:.....	8
3.3	CMH Modications.	9
4	Testing Details.....	10

1 Introduction

From Customer:

“It should be better to be able to have a non blocking D command for voice calls even with the +CSSN command active. This behaviour can be defined by a new at command at startup or directly by default in the modem.

TI 2004-06-03:

A new %CSSN command will be implemented.”

The understanding of this requirement is as follows:

ATD behaves in most of the cases in a non-blocking way. After executing ATD, the OK will return immediately, as, for example, in the following scenario:

```
atd03039831181;
```

```
OK
```

```
NO CARRIER
```

There is however a couple of scenarios in which ATD behave in a blocking way. These are:

- When there is a pending +CSSI intermediate result code. (And +CSSN=1)
- When +COLP has been enabled.
- When the call has been started by SAT.

This issue applies to the first scenario. The current behaviour in that scenario will be:

```
+CSSN=1
```

```
OK
```

```
atd03039831181;
```

```
+CSSI: 1
```

```
OK
```

The OK will only be sent from the ACI when the Called Party has accepted the call.

The required behaviour is, however,

```
%CSSN=1
```

OK

atd03039831181;

OK

+CSSI: 1

To handle this functionality, a new AT Command will be created, %CSSN. This Command will enable a mode in which +CSSI will not block ATD. %CSSN will have the same parameters and responses as +CSSN (<n> and <m> in GSM. 07.07), plus a new value for the parameter <n>, as described below.

2 Interface changes.

2.1 Supplementary service notifications %CSSN

%CSSN parameter command syntax

Command	Possible response(s)
%CSSN= [<n> [, <m>]]	
%CSSN?	%CSSN: <n> , <m>
%CSSN=?	%CSSN: (list of supported <n>s) , (list of supported <m>s)

Defined values

<n> (parameter sets/shows the +CSSI result code presentation status in the TA):

0 disable

1 enable

2 *enable and non-blocking atD* (Added value to parameter <n>)

<m> (parameter sets/shows the +CSSU result code presentation status in the TA):

0 disable

1 enable

This parameter will have the same functionality as +CSSN, defined in 3GPP 27.007, version 3.13, section 7.17, plus the added value to the parameter <n>

The ACI document 8415_004.doc will also be updated.

3 Proposed Low Level Design.

3.1 Interface Changes

The new command %CSSN will be defined as described above.

3.2 ATI Modifications.

3.2.1 New Functions:

- setatPercentCSSN(). It will handle the %CSSN command.
- queatPercentCSSN(). It will handle the “%CSSN?” command.
- atiSShandleCSSN(). It will contain the common functionality of +CSSN and %CSSN.

3.2.2 Modified Functions:

- setatPlusCSSN().

3.2.3 Affected Global variables:

- ati_user_output_cfg[.CSSI_stat. This variable will accept the value “2” when %CSSN=2 is set, and will be accessed by CMH.
- The ATI array "cmds", in the file ati_cmd.c, will be updated with the new functions setatPercentCSSN() and queatPercentCSSN().

3.2.4 Description of the changes:

- Function atiSShandleCSSN (char *c1, UBYTE srcId); It will contain the main body of the current function setatPlusCSSN(), and will be called by setatPercentCSSN() and setatPlusCSSN(), because it encapsulates their common functionality (In order to avoid duplication of code).
- Function setatPercentCSSN(char *c1, UBYTE srcId); It will check that the first character of “*c1” (CSSI mode) is within the valid range (“0”, “1” or “2”), and then will call atiSShandleCSSN().
- Function setatPlusCSSN() will be modified so that it checks that the first character of “*c1” (CSSI mode) is within the valid range (“0”, “1”), and then will call atiSShandleCSSN().

-Function queatPercentCSSN(). It will call the function resp_disp() with the 2 parameters required.

3.3 CMH Modications.

No modification required. When ati_user_output_cfg[].CSSI_stat =2, the OK will be sent immediately by cmhCC_atdsendok(), and the CSSI will be handled afterwards by rCI_PlusCSSI().

4 Testing Details

The following Windows test cases will be added:

-Testcase 1. Test % CSSN=0 (CSSI presentation disabled)

AT+CPIN=1

OK

AT+COPS=0

OK

AT% CSSN=0

ATD03039831181;

OK

-Testcase 2. Test % CSSN=1(CSSI presentation enabled and blocking atD)

AT+CPIN=1

OK

AT+COPS=0

OK

AT% CSSN=1

OK

ATD03039831181;

+CSSI: 1

OK

-Testcase 3. Test % CSSN=2(CSSI presentation enabled and non-blocking atD)

AT+CPIN=1

OK

AT+COPS=0

OK

AT% CSSN=2

OK

ATD03039831181;

OK

+CSSI: 1

-Testcase 4. Test % CSSN=2,1 (CSSI and CSSU presentation enabled and non-blocking atD)

AT+CPIN=1

OK

AT+COPS=0

OK

AT%CSSN=2

OK

ATD03039831181;

OK

+CSSI: 1

+CSSU: 1

-Testcase 5. Set and query %CSSN with different values.

AT+CPIN=1

OK

AT+COPS=0

OK

AT%CSSN=2,1

OK

AT%CSSN?

%CSSN 2,1

AT%CSSN=3

CME

Similar functionality will be tested in the target.