



Message Sequence Charts

AS_GPRS_MSC_Measurements Document

Department:	TID
Creation Date:	05 February, 2004
Last Modified:	10 March, 2004 by Bernd Saborrosch
ID and Version:	8010.xxx.01.002
Status:	Accepted

Copyright © 2004 Texas Instruments, Inc. All rights reserved.

Texas Instruments Proprietary Information

Under Non-Disclosure Agreement – Do Not Copy

0 Document Control

Copyright © 2004 Texas Instruments, Inc.

All rights reserved.

Texas Instruments Incorporated and / or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and / or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and / or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and / or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and / or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and / or the licensing of software do not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of TI.

0.1 Document History

ID	Author	Date	Status
8010.xxx.01.001	SAB	05 February, 2004	Being Processed
8010.xxx.01.002	SAB	10 March, 2004	Accepted

0.2 References, Abbreviations, Terms

[TI 8010.801] 8010.801, "References and Abbreviations (UMTS)", Texas Instruments

Table of Contents

1	Introduction.....	5
2	Uplink Power Control.....	6
2.1	Parameters.....	6
2.1.1	C-Value	6
2.1.1.1	Packet Idle Mode	6
2.1.1.2	Packet Transfer Mode.....	6
2.1.2	Power Control Parameters Γ_0 and α	7
2.2	Design Approach	7
2.2.1	C-Value	7
2.2.2	Power Control Parameters Γ_0 and α	8
2.2.2.1	Confirmation CGRLC_PWR_CTRL_CNF	8
2.2.2.2	L1 Access to Uplink Power Control Levels	8
2.2.3	Common Library	9
2.3	Scenarios.....	10
2.3.1	Static Packet Idle Mode.....	10
2.3.2	Static Packet Transfer Mode	11
2.3.3	Transition from Packet Idle to Packet Transfer Mode	12
2.3.3.1	Single Block Procedure	12
2.3.3.2	TBF Establishment.....	13
2.3.3.3	Access to Uplink Power Control Levels	15
2.3.4	Transition from Packet Transfer to Packet Idle Mode	16

1 Introduction

This document is a part of the high level documentation for the dual mode GSM/GPRS and UMTS protocol stack development project. It contains a set of Message Sequence Charts (MSCs) illustrating communication between entities of the protocol stack dependent on access technology, as well as the communication from these entities to parts of the protocol stack considered independent of access technology (the Non-Access Stratum (NAS)) and to the Physical Layer (PHY).

In all MSCs entities will only be shown if they are involved in the sequence illustrated. Sub-MSCs may be used to show a sequence used in more than one context, or used repetitively. In cases where sub-MSCs are used, the sub-MSC may include more or less entities than the MSC referring to it, if some entities are only relevant to the sub-MSC or to the referring MSC.

This document is split into sections containing MSCs illustrating scenarios related to each other. The scenarios included in this document are concerned mainly with the data transfer. The meaning of each MSC should be clear of the title and the small description, in the beginning of each MSC.

2 Uplink Power Control

2.1 Parameters

The uplink power control algorithm applied by the MS is specified in the 3GPP TS 05.08.

“The RF output power, P_{CH} , to be employed by the MS on each individual uplink PDCH shall be:

$$P_{CH} = \min(\Gamma_0 - \Gamma_{CH} - \alpha * (C + 48), P_{MAX}),$$

where

Γ_{CH}	is an MS and channel specific power control parameter, sent to the MS in an RLC control message (see 3GPP TS 04.60).
Γ_0	= 39 dBm for GSM900 = 36 dBm for DCS1800
α	is a system parameter, broadcast on PBCCH or optionally sent to MS in an RLC control message (see 3GPP TS 04.08 and 3GPP TS 04.60).
C	is the normalised received signal level at the MS as defined in 10.2.3.1.
P _{MAX}	is the maximum allowed output power in the cell = GPRS_MS_TXPWR_MAX_CCH if PBCCH exists MS_TXPWR_MAX_CCH otherwise”

[extracted from 3GPP TS 05.08]

2.1.1 C-Value

The C-value is calculated in different ways in packet idle and packet transfer mode.

2.1.1.1 Packet Idle Mode

In packet idle mode the C-value is derived from the received signal level of the PCCCH or, if PCCCH is not existing, the BCCH.

New receive signal level measurements are provided by the L1 approximately every 1 second. Measurements are stopped on transition to packet transfer mode. When entering packet idle mode, the C-value calculation shall continue from the C-value obtained during packet transfer mode.

C-value is used for the following purposes:

- The C-value derived in packet idle mode shall be used to calculate the output power when the MS transfers its first radio block (this block could be the first block of an uplink TBF or an uplink single block).
- Packet Resource Request Message

2.1.1.2 Packet Transfer Mode

In packet transfer mode the C-value is derived from the same received signal level measurements on the BCCH carrier of the serving cell as made for cell reselection. If indicated by the parameter PC_MEAS_CHAN, the MS shall instead derive the C-value from the received signal level of each radio block on one of the PDCH monitored by the MS for PACCH.

[!!!SAB!!!] When in packet transfer mode GRLL currently uses the receive signal level measurement of the

serving cell included in the MPHP_TCR_MEAS_IND primitive for cell re-selection purposes, but the receive signal level measurement provided with the function maca_power_control for deriving the C-value. This is a mismatch with specification requirement. Advice is needed.

New receive signal level measurements are provided by the L1 approximately every 20 millisecond. Measurements are started as soon as TBF starting time elapsed and stopped on transition to packet idle mode. When entering packet transfer mode, the C-value calculation shall continue from the C-value obtained during packet idle mode.

C-value is in the following RLC/MAC control messages:

- Packet Downlink Ack/Nack Message – Channel Quality Report
- Packet Resource Request Message

2.1.2 Power Control Parameters Γ_0 and α

Γ_0 and α are MS and channel specific power control parameters used to calculate the uplink output power. They are sent to the MS in the following RLC/MAC control messages:

Packet Downlink Assignment

Packet Power Control / Timing Advance

Packet System Information 1

(Packet) System Information 13

Packet Uplink Ack/Nack

Packet Uplink Assignment

Packet Timeslot Reconfigure

PDCH Assignment Command

Packet Immediate Assignment

When receiving new power control parameters the MS is required to react to it latest after a reaction time of three blocks.

2.2 Design Approach

2.2.1 C-Value

The C-value is calculated by RR in case of packet idle mode and by GRLC in case of packet transfer mode. In packet idle mode the receive signal level included either in the MPHC_DATA_IND with l2_channel equal to L2_CHANNEL_PCH or in the MPHP_DATA_IND with l2_channel equal to L2_PCHANNEL_PPCH is used for C-value calculation. In packet transfer mode the information included in the parameter of the function maca_power_control is used.

There are four different modes of operation for the C-value derivation:

- Static Packet Idle Mode

The C-value is updated by RR every time new measured values are provided.

- Static Packet Transfer Mode

The C-value is updated by GRLC every time new measured values are provided. Along with it, the uplink power control levels are updated.

- Transition from Packet Idle to Packet Transfer Mode

As soon as a starting time is running (either triggered by an uplink single block procedure or by a TBF with a present starting time) any updated C-value is forwarded from RR to GRLLC in order to update the uplink power control levels.

In case no starting time is present, but a TBF request is currently processed by L1, any updated C-value is forwarded from RR to GRLLC in order to update the uplink power control levels.

- Transition from Packet Transfer to Packet Idle Mode

When leaving packet transfer mode the last obtained C-value is forwarded from GRLLC to RR in order to pass control to this entity.

2.2.2 Power Control Parameters Γ_0 and α

Every RLC/MAC control message is forwarded to and decoded by RR. Decoding will be done only in RR due to timing constraint in GRLLC.

In case power control parameters are included in the message they are passed back to GRLLC by sending a primitive. This primitive currently does not exist when the MS is packet transfer mode and shall be defined in the CGRLLC SAP. Just when changing from packet idle to packet transfer mode the primitives CGRLLC_DL_TBF_REQ and CGRLLC_UL_TBF_RES could be re-used by adding a specific sub-structure.

GRLLC shall store the power control parameters for further processing.

When starting any uplink single block procedure (either two phase access or single block without TBF establishment) or in case a TBF with or without a present starting time is triggered by the network, the uplink power control levels shall be recalculated by GRLLC any time new power control parameters are received and the starting time is not yet elapsed. L1 will retrieve the uplink power control levels by calling the function `maca_power_control` just at the starting time. Neither GRLLC nor RR are aware of the point in time the starting time will elapsed, that's why GRLLC always shall re-calculate the uplink power control levels if it receives new power control parameters.

2.2.2.1 Confirmation CGRLLC_PWR_CTRL_CNF

L23 is responsible for providing correct uplink power control levels in case an uplink single block shall be sent to the network or a TBF shall be established. L1 retrieves the uplink power control level by a call to the function `maca_power_control` right before the uplink single block shall be sent or the TBF shall start. L23 has no control of that point in time. That's why L23 has to provide the correct power levels before requesting any uplink single block by means of the MPHP_SINGLE_BLOCK_REQ primitive or a TBF by means of the MPHP_ASSIGNMENT_REQ primitive. Just in these cases a confirmation CGRLLC_PWR_CTRL_CNF is needed.

See also scenarios 'Single Block Procedure' and 'TBF Establishment' to get some more details about the applied message sequence.

2.2.2.2 L1 Access to Uplink Power Control Levels

[!!!SAB!!!] Please note that this chapter has nothing to do with the shared memory concept currently implemented in the GRLLC entity. It is a general memory access violation that may occur due to the mechanism of calling a function in a primitive based system.

To avoid that L1 reads the buffer holding the uplink power control levels currently processed by GRLLC (in case an uplink single block procedure is running or a TBF is going to be established or the GRLLC internal signal MAC_PWR_CTRL_IND cannot be processed within 20 milliseconds), the buffer shall be hold

doubled and shall be protected. The protection shall be not realised by a semaphore, but at least by using a flag which can be set in GRLC by an atomic operation. The flag determines which buffer to use by L1.

See also scenario




Figure 5 - TBF Establishment – Part 2

Access to Uplink Power Control Levels' to get some more details about the applied message sequence.

2.2.3 Common Library

As the GRLC entity shall be used in several different projects any use of functions located in the common library and called from several entities possibly at the same time shall be avoided. Any direct call of functions not located in the GRLC but in other protocol stack entities shall be avoided.

2.3 Scenarios

2.3.1 Static Packet Idle Mode




Figure 1 - Static Packet Idle Mode

2.3.2 Static Packet Transfer Mode




Figure 2 - Static Packet Transfer Mode

2.3.3 Transition from Packet Idle to Packet Transfer Mode

2.3.3.1 Single Block Procedure




Figure 3 - Single Block Procedure

2.3.3.2 TBF Establishment




Figure 4 - TBF Establishment – Part 1




Figure 5 - TBF Establishment – Part 2

2.3.3.3 Access to Uplink Power Control Levels




Figure 6 - Access to Uplink Power Control Levels

2.3.4 Transition from Packet Transfer to Packet Idle Mode




Figure 7 - Transition from Packet Transfer to Packet Idle Mode