



Technical Document

GSM DATA SERVICES
MESSAGE SEQUENCE CHARTS
RA1'

Document Number:	6148.203.97.100
Version:	0.2
Status:	Draft
Approval Authority:	
Creation Date:	1997-Mar-12
Last changed:	2015-Mar-08 by XGUTTEFE
File Name:	ra1.doc

Important Notice

Texas Instruments Incorporated and/or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and/or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and/or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and/or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and/or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and/or the licensing of software does not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronically or mechanically, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

Date	Changed by	Approved by	Version	Status	Notes
1997-Mar-12	LE		0.1		1
2003-May-26	XGUTTEFE		0.2	Draft	

Notes:

1. Initial version

Table of Contents

1	General	4
1.1	References	4
1.2	Abbreviations	8
1.3	Terms	9
2	Overview	10
3	Introduction	12
3.1	Frame Formats	12
3.2	Extension Bits	13
3.3	Status Bits	15
4	Common Procedures	16
4.1	Activation / Deactivation	16
4.2	Setting of Baudrate	16
4.3	Status Change	17
5	Transmission of data	18
6	Reception of data	19
	Appendices	20
A.	Acronyms	20
B.	Glossary	20

List of Figures and Tables

List of References

- | | |
|-----------------|---|
| [ISO 9000:2000] | International Organization for Standardization. Quality management systems - Fundamentals and vocabulary. December 2000 |
|-----------------|---|

1 General

1.1 References

- [1] GSM 2.81, Line Identification Supplementary Services - Stage 1
ETS 300 514, ETSI, September 1994
- [2] GSM 2.82, Call Forwarding Supplementary Services - Stage 1
ETS 300 515, ETSI, September 1994
- [3] GSM 2.83, Call Waiting and Call Hold Supplementary Services - Stage 1
ETS 300 516, ETSI, September 1994
- [4] GSM 2.84, Multi Party Supplementary Services - Stage 1
ETS 300 517, ETSI, September 1994
- [5] GSM 2.85, Closed User Group Supplementary Services - Stage 1
ETS 300 518, ETSI, September 1994
- [6] GSM 2.86, Advice of Charge Supplementary Services - Stage 1
ETS 300 519, ETSI, September 1994
- [7] GSM 2.88, Call Barring Supplementary Services - Stage 1
ETS 300 520, ETSI, September 1994
- [8] GSM 3.14, Support of Dual Tone Multi Frequency Signalling via the GSM System
ETS 300 532, ETSI, April 1994
- [9] GSM 3.40, Technical Realization of the Short Message Service Point-to-Point
ETS 300 536, ETSI, January 1996
- [10] GSM 3.41, Technical Realization of Short Message Service Cell Broadcast
ETS 300 537, ETSI, June 1995
- [11] GSM 3.81, Line Identification Supplementary Services - Stage 2
ETS 300 542, ETSI, February 1995
- [12] GSM 3.82, Call Forwarding Supplementary Services - Stage 2
ETS 300 543, ETSI, February 1995
- [13] GSM 3.83, Call Waiting and Call Hold Supplementary Services - Stage 2
ETS 300 544, ETSI, November 1994
- [14] GSM 3.84, Multi Party Supplementary Services - Stage 2
ETS 300 545, ETSI, November 1994
- [15] GSM 3.85, Closed User Group Supplementary Services - Stage 2
ETS 300 546, ETSI, January 1996
- [16] GSM 3.86, Advice of Charge Supplementary Services - Stage 2
ETS 300 547, ETSI, March 1995
- [17] GSM 3.88, Call Barring Supplementary Services - Stage 2
ETS 300 548, ETSI, November 1994
- [18] GSM 4.01, MS-BSS Interface General Aspects and Principles
ETS 300 550, ETSI, September 1994
- [18] GSM 4.03, MS-BSS Interface Channel Structures and Access Capabilities
ETS 300 552, ETSI, September 1994
- [19] GSM 4.05, Data Link Layer General Aspects
ETS 300 554, ETSI, September 1994
- [20] GSM 4.06, MS-BSS Interface Data Link Layer Specification
ETS 300 555, ETSI, September 1994

- [21] GSM 4.07, Mobile Radio Interface Signalling Layer 3 General Aspects
ETS 300 556, ETSI, February 1995
- [22] GSM 4.08, Mobile Radio Interface Layer 3 Specification
ETS 300 557, ETSI, January 1996
- [23] GSM 4.10, Mobile Radio Interface Layer 3 Supplementary Services Specification
General Aspects
ETS 300 558, ETSI, February 1995
- [24] GSM 4.11, Point-to-Point Short Message Service Support on Mobile Radio Interface
ETS 300 559, ETSI, October 1995
- [25] GSM 4.12, Short Message Service Cell Broadcast Support on Mobile Radio Interface
ETS 300 560, ETSI, January 1996
- [26] GSM 4.80, Mobile Radio Interface Supplementary Services Specification Formats and Coding
ETS 300 564, ETSI, February 1995
- [27] GSM 4.81, Line Identification Supplementary Services - Stage 3
ETS 300 565, ETSI, February 1995
- [28] GSM 4.82, Call Forwarding Supplementary Services - Stage 3
ETS 300 566, ETSI, February 1995
- [29] GSM 4.83, Call Waiting and Call Hold Supplementary Services - Stage 3
ETS 300 567, ETSI, February 1995
- [30] GSM 4.84, Multi Party Supplementary Services - Stage 3
ETS 300 568, ETSI, February 1995
- [31] GSM 4.85, Closed User Group Supplementary Services - Stage 3
ETS 300 569, ETSI, February 1995
- [32] GSM 4.86, Advice of Charge Supplementary Services - Stage 3
ETS 300 570, ETSI, February 1995
- [33] GSM 4.88, Call Barring Supplementary Services - Stage 3
ETS 300 571, ETSI, February 1995
- [34] GSM 5.01, Physical Layer on the Radio Path General Description
ETS 300 573, ETSI, October 1995
- [35] GSM 5.02, Multiplexing and Multiple Access on the Radio Path
ETS 300 574, ETSI, January 1996
- [36] GSM 5.08, Radio Sub-system Link Control
ETS 300 578, ETSI, January 1996
- [37] GSM 5.10, Radio Sub-system Synchronisation
ETS 300 579, ETSI, October 1995
- [38] Service Access Point MMREG
6147.100.96.100; Condat GmbH, December 1996
- [39] Service Access Point MNCC
6147.101.96.100; Condat GmbH, December 1996
- [40] Service Access Point MNSS
6147.102.96.100; Condat GmbH, December 1996
- [41] Service Access Point MNSMS
6147.103.96.100; Condat GmbH, December 1996
- [42] Service Access Point MMCC
6147.104.97.100; Condat GmbH
- [43] Service Access Point MMSS
6147.105.97.100; Condat GmbH

- [44] Service Access Point MMSMS
6147.106.97.100; Condat GmbH
- [45] Service Access Point RR
6147.107.97.100; Condat GmbH
- [46] Service Access Point SIM
6147.108.97.100; Condat GmbH
- [47] Service Access Point MPH
6147.109.96.100; Condat GmbH, December 1996
- [48] Service Access Point DL
6147.110.96.100; Condat GmbH, December 1996
- [49] Service Access Point MDL
6147.111.96.100; Condat GmbH, December 1996
- [50] Service Access Point PH
6147.112.96.100; Condat GmbH, December 1996
- [51] Service Access Point MMI
6147.113.96.100; Condat GmbH, December 1996
- [52] Message Sequence Charts CC
6147.200.97.100; Condat GmbH
- [53] Message Sequence Charts SS
6147.201.97.100; Condat GmbH
- [54] Message Sequence Charts SMS
6147.202.97.100; Condat GmbH
- [55] Message Sequence Charts MM
6147.203.97.100; Condat GmbH
- [56] Message Sequence Charts RR
6147.204.96.100; Condat GmbH, December 1996
- [57] Message Sequence Charts DL
6147.205.96.100; Condat GmbH, December 1996
- [58] Users Guide
6147.300.96.100; Condat GmbH, December 1996
- [59] Test Specification CC
6147.400.97.100; Condat GmbH
- [60] Test Specification SS
6147.401.97.100; Condat GmbH
- [61] Test Specification SMS
6147.402.97.100; Condat GmbH
- [62] Test Specification MM
6147.403.97.100; Condat GmbH
- [63] Test Specification RR
6147.404.97.100; Condat GmbH
- [64] Test Specification DL
6147.405.97.100; Condat GmbH
- [65] Test Specification CCD
6147.406.97.100; Condat GmbH
- [66] SDL Specification CC
6147.500.97.100; Condat GmbH

- [67] SDL Specification SS
6147.501.97.100; Condat GmbH
- [68] SDL Specification SMS
6147.502.97.100; Condat GmbH
- [69] SDL Specification MM
6147.503.97.100; Condat GmbH
- [70] SDL Specification RR
6147.504.97.100; Condat GmbH
- [71] SDL Specification DL
6147.505.97.100; Condat GmbH
- [72] Message Specification CC
6147.600.97.100; Condat GmbH
- [73] Message Specification SS
6147.601.97.100; Condat GmbH
- [74] Message Specification SMS
6147.602.97.100; Condat GmbH
- [75] Message Specification MM
6147.603.97.100; Condat GmbH
- [76] Message Specification RR
6147.604.97.100; Condat GmbH
- [77] Message Specification DL
6147.605.97.100; Condat GmbH
- [78] Technical Documentation CC
6147.700.97.100; Condat GmbH
- [79] Technical Documentation SS
6147.701.97.100; Condat GmbH
- [80] Technical Documentation SMS
6147.702.97.100; Condat GmbH
- [81] Technical Documentation MM
6147.703.97.100; Condat GmbH
- [82] Technical Documentation RR
6147.704.97.100; Condat GmbH
- [83] Technical Documentation DL
6147.705.97.100; Condat GmbH
- [84] Technical Documentation CCD
6147.706.97.100; Condat GmbH

1.2 Abbreviations

AGCH Access Grant Channel

1.3 Terms

Entity	Program which executes the functions of a layer
Message:	A message is a data unit which is transferred between the entities of the same layer (peer-to-peer) of the mobile and infrastructure side. Message is used as a synonym to protocol data unit (PDU). A message may contain several information elements.
Primitive:	A primitive is a data unit which is transferred between layers on one component (mobile station or infrastructure). The primitive has an operation code which identifies the primitive and its parameters.
Service Access Point:	A Service Access Point is a data interface between two layers on one component (mobile station or infrastructure).

2 Overview

The GSM specifications are normative when used to describe the functionality of interfaces, but the stacks and




Figure 1: Data Services protocol architecture

This document describes the services offered by the radio link protocol.

3 Introduction

3.1 Frame Formats

The channel codec requests in regular times data from the rate adaption function RA1'.

- For 9600 bit/s 60 bit CCITT V.110 frames are send to the channel codec.
- For 4800 bit/s 60 bit CCITT V.110 frames are send to the channel codec.
- For 2400 bit/s 36 bit CCITT V.110 frames are send to the channel codec.

The number of blocks send to channel codec depends on the time interval and the baudrate:

Baudrate	Time Interval			Type of Frame
	5 ms	10 ms	20 ms	
9600 bit/s	1	2	4	60 bit V.110
4800 bit/s	-	1	2	60 bit V.110
2400 bit/s	-	1	2	36 bit V.110

If the channel codec requests all 10 ms data at 9600 bit/s the rate adaption function RA1' sends 100 times per second two 60 bit V.110 frames. This is an air interface rate of 12000 bit/s. The data inside one 60 bit V.110 frame is 48 bits. So $100 * 2 * 48$ data bits are send per second. This is equal to the baudrate of 9600 bits/s.

Using longer intervals reduces communication between rate adaption function RA1' and channel co-
dec but prolongs the reaction time for in-band flow control (status bits).

If the number of stored bits for sending to channel codec is lower than a threshold the rate adaption
function RA1' requests new data from it's source (RLP, RA0 or fax adapter).

The following frame formats are defined:

9600 bit/s and 4800 bit/s (60 bit CCITT V.110 frames)

Offset	7	6	5	4	3	2	1	0
0	D7	S1	D6	D5	D4	D3	D2	D1
1	D14	D13	x	D12	D11	D10	D9	D8
2	D21	D20	D19	S3	D18	D17	D16	D15
3	E7	E6	E5	E4	S4	D24	D23	D22
4	D31	S6	D30	D29	D28	D27	D26	D25
5	D38	D37	x	D36	D35	D34	D33	D32
6	D45	D44	D43	S8	D42	D41	D40	D39
7	0	0	0	0	S9	D48	D47	D46

2400 bit/s (blocks of 36 bit CCITT V.110 frames)

Offset	7	6	5	4	3	2	1	0
0	x	D6	D5	D4	S1	D3	D2	D1
1	S4	D12	D11	D10	S3	D9	D8	D7
2	S6	D15	D14	D13	E7	E6	E5	E4
3	S8	D21	D20	D19	x	D18	D17	D16
4	0	0	0	0	S9	D24	D23	D22

3.2 Extension Bits

The extension bits E4, E5, E6 and E7 are inserted in each V.110 frames. E4, E5 and E6 are used as clocking bits and E7 is the multiframe bit.

Synchronous data signals received by the MT from the DTE at the MS or by IWF from the modem on the PSTN may not be synchronized to the PLMN. The following method shall be used to enable transfer of those data signals and the corresponding bit timing information via the V.110 frames. Such a situation would exist where the signals received from the modem at the IWF require its own clock or where the signals received from the DTE at the MS employs its own network independent clock. The transmitting end of the GSM PLMN connection shall establish a multiframe structure utilising bit E7 consisting of four frames by setting E7 in every fourth frame to binary 0. This structure is identical to all user rates. The frame synchronization will be achieved and maintained during the entire call so that corrections for the network independent clocking by the receiving end of the GSM PLMN connection can be easily recognized and applied based on the code words (in c1, c2, c3, c4 and c5) positioned in bits E4, E5 and E6 of two consecutive V.110 frames as depicted in the next figure. Thus, the multiframe structure allows for one 5-bit code words to be transmitted every two V.110 frames for the purposes of network independent clocking. The two code-words may be different from each other within the multiframe.

Frame	E4	E5	E6	E7
Multiframe 0a	c1	c2	1	0
Multiframe 1a	c3	c4	c5	1
Multiframe 0b	c1	c2	1	1
Multiframe 1b	c3	c4	c5	1

Once multiframe synchronization is achieved, each code word is independently evaluated to determine the compensation needed, if any. The compensation is carried out after reception of multiframe 1a or 1b.

The V.110 transmitter will use the following 5-bit code words, as shown in the next figure, to indicate the four possible states of compensation required for network independent clocking.

	c1	c2	c3	c4	c5
No compensation	1	1	1	1	1
Negative compensation	1	0	0	1	0
Positive compensation of a zero	0	1	0	0	1
Positive compensation of one	0	0	1	0	0

When negative compensation is indicated, one less user data bit than normal is transported in the accepted frame (multiframe 1a or multiframe 1b). A negative compensation shall cause the receiver to delete the user data bit occupied by bit position D25, since the transmitter sets this to binary 1 and does not utilize this position for user data. At those user data rates where the user data bit repeated, all copies of D25 shall be discarded.

When a positive compensation is indicated, one additional user data bit is transferred by means of the code word. At the receiver, a positive compensation will cause a user data bit of binary 0 or 1, as indicated by the code word, to be inserted between the user data bits carried in bit positions D24 and D25 (in multiframe 1a or 1b) of the V.110 frame.

When no compensation is necessary or when NIC is applied, the values of E4, E5, E6 and E7 on the four multi frame scheme is

Frame	E4	E5	E6	E7
Multiframe 0a	1	1	1	0
Multiframe 1a	1	1	1	1
Multiframe 0b	1	1	1	1
Multiframe 1b	1	1	1	1

When NIC is not applicable the MS and the IWF shall disregard the received value of bits E4, E5, E6 and E7 in the data transmission phase. NIC is not applicable in the following cases:

- transparent asynchronous bearer services
- the facsimile teleservices in transparent mode
- every transparent bearer services when interworking with an UDI information transfer capability

3.3 Status Bits

The bits S and X are used to convey channel status information associated with the data bits in the data transfer state. The S-Bits are put in two groups SA and SB to carry the condition of two interchange circuits. The X-bit is used to control the condition of circuit 106.

For the S and X bits, a binary zero corresponds to ON condition, a binary one to the OFF condition.

The status SA corresponds with S1, S3, S6 and S8. Status SB is defined by S4 and S9. The following figure shows the use of SA, SB and X and the corresponding flow control signals:


Terminal Equipment	Interworking Function	Terminal Equipment
DTR	SA	DSR
RTS	SB	DCD
CTS	X	CTS

The mobile station uses DTR to signal that it is ready for operation. The RTS signal is used to indicate that the mobile station will send data. The CTS signal is used to indicate whether it is possible to receive data or not.

The interworking function uses DSR to indicate that the other party is connected. DCD is used to indicate that data will be sent to the mobile station. CTS is used by the interworking function to indicate that it is ready for receiving data.

4 Common Procedures

4.1 Activation / Deactivation




(RA1 1)
The rate adaption function 1' is activated or deactivated.

(CHC 1)

The information is forwarded to the channel codec.

4.2 Setting of Baudrate




(RA1 1)

A new speed rate is defined.

(CHC 1)

The information is forwarded to the channel codec.

4.3 Status Change




The AT command interpreter indicates a change of status. This results in change of setting in S and X bits in the following V.110 frames.

(AT 1)

After receiving information with V.100 frames the status bits have changed. The new status is signalled to the AT command interpreter.

5 Transmission of data

Transmission of data is only processed, when the rate adaption function RA1' is activated.



The channel codec requests new data.

(CHC 1)

From previous received V.110 frames it is detected that the interworking function is not able to receive data. Rate adaption function RA1' retransmits the last sent V.110 frame to the interworking function to avoid loss of synchronisation and to forward it's own status.

(CHC 2)

From previous received V.110 frames it is detected that the interworking function is able to receive data. Rate adaption function RA1' builds the next frame(s) and sends it to the channel coded.

(S 1)


If the remaining number of bits is lower than a configurable threshold value, the rate adaption function RA1' requests new data from it's source. This is the FAD, RLP or RA0.

(RA1 2)

New data is stored at rate adaption function 1'.

6 Reception of data

Reception of data is only processed, when the rate adaption function RA1' is activated.



The channel codec sends V.110 frames to the rate adaption function RA1'. The status and extension bits are extracted.

(S 1)

If the rate adaption function is able to receive data, the data is forwarded to the source. The source is the fax adapter, the radio link protocol or the rate adaption function 0.

(RA1 2)

The channel codec sends V.110 frames to the rate adaption function RA1'. The status and extension bits are extracted. If the rate adaption function is unable to receive data, the data is erased.

Appendices

A. Acronyms

DS-WCDMA Direct Sequence/Spread Wideband Code Division Multiple Access

B. Glossary

International Mobile Telecommunication 2000 (IMT-2000/ITU-2000) Formerly referred to as FPLMTS (Future Public Land-Mobile Telephone System), this is the ITU's specification/family of standards for 3G. This initiative provides a global infrastructure through both satellite and terrestrial systems, for fixed and mobile phone users. The family of standards is a framework comprising a mix/blend of systems providing global roaming. <URL: <http://www.imt-2000.org/>>