



Technical Document

EOTD LC CONTROLLER

DESIGN SPEC

Document Number:	8443.714.02.004
Version:	0.5
Status:	Draft
Approval Authority:	
Creation Date:	2002-Oct-08
Last changed:	2015-Mar-08 by XGUTTEFE
File Name:	8443_714_02_EOTD_Lccontroller.doc

Important Notice

Texas Instruments Incorporated and/or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and/or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and/or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and/or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and/or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and/or the licensing of software does not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronically or mechanically, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

Date	Changed by	Approved by	Version	Status	Notes
2002-Jul-05	OTH		0.1	Planned	1
2002-Sep-13	LOL		0.2	Planned	
2002-Sep-23	LOL		0.3	Being Processed	
2002-Sep-27	LOL		0.4	Submitted	
2003-May-08	XGUTTEFE		0.5	Draft	

Notes:

1. Initial version

Table of Contents

0.1	References, Abbreviations, Terms	4
1	Introduction	4
A.1	Blockdiagram of the software structure	4
1.1	Service Access Points	5
1.2	Controller.....	5
1.3	Cursor module	5
2	LC Controller	5
2.1	State Machine	5
2.2	State / event table	7
3	Functionality	7
3.1	SMS request.....	8
3.1.1	SMS request, no measurement data	8
3.1.2	SMS request, measurement data stored.	9
3.2	RRLP request	10
3.2.1	RRLP request, no measurement data	10
3.2.2	RRLP request, measurement data stored	11
3.2.3	RRLP request, serving BTS not reference BTS	12
3.2.4	RRLP request, location method not supported	13
3.2.5	RRLP request, handover during measurements	14
3.3	Periodic measurement.....	14
4	CPS Algorithm	14
Appendices.....		16
A.	Acronyms	16
B.	Glossary	16

List of Figures and Tables

List of References

- | | |
|-----------------|---|
| [ISO 9000:2000] | International Organization for Standardization. Quality management systems - Fundamentals and vocabulary. December 2000 |
|-----------------|---|

0.1 References, Abbreviations, Terms

[TI 7010.801] 7010.801, References and Vocabulary, Texas Instruments

[8443_716_02_EOTD_RRLP.doc]

E-OTD RRLP, Low Level Design specification, Condat AG

[3GPP_04.31] 3rd Generation Partnership Project; Technical Specification Group GSM EDGE Radio Access Network; Location Services (LCS); Mobile Station (MS) – Serving Mobile Location Centre (SMLC); Radio Resource LCS Protocol (RRLP), (V8.8.0 Release 1999)

[C_7010.801] 7010.801, References and Vocabulary, Condat AG

[8443_713_02_EOTD_SystemArchitecture.doc]

E-OTD System Architecture, High level design specification, Condat AG

[CU0239] Cursor Standard Log Format, Issue 1.0, January 2002

1 Introduction

This document defines the functionality of the Location Service Controller and Cursor Bridge in more detail. The overall E-OTD design on a general level is described in [8443_713_02_EOTD_SystemArchitecture.doc]. The RRLP module is described in [8443_716_02_EOTD_RRLP.doc].

A.1 Blockdiagram of the software structure




Figure 1: LC details

Figure 1 shows the details of the Location Service module. All positioning calculations and algorithms are based on the Cursor module, provided by CPS. It consists of two parts, the Cursor Algorithm and the Cursor Bridge code. To have a more generic approach for further developments, the LC controller

co-ordinates the positioning requests to the appropriate implementation, e.g. E-OTD or GPS. Condat will develop the LC controller and the RRLP. The Cursor Bridge code is available in source code, representing the interface between the LC controller and the Cursor Algorithm. It is used to exemplify the data handling between the modules but will be adapted to the Condat needs. The Cursor Algorithm module is provided in object code, receiving the correlation data and BTS identifier and calculates precise OTD values. The interface between LC controller and RRLP is primitive based with functional character in order to allow running RRLP in other task context, e.g. RR.

1.1 Service Access Points

The LC Controller block and the RRLP block inside the LC module is assigned to a new task. Following new entities are defined:

LC – for the LC Controller
RRLP – for the new protocol

- with the respective SAP's:
- RRLP – communication between RR and RRLP.
- RRLC – communication between RR and LC controller.
- RRLP – communication between LC controller and RRLP
- MNLC – communication between LC controller and ACI during test and demonstration.

The definition of these SAP's can be found in [8443_713_02_EOTD_SystemArchitecture.doc].

The Cursor module, i.e. Cursor Bridge and Cursor Algorithm, will not be implemented as a separate entity. Instead it will be implemented as part of the LC Controller.

1.2 Controller

The controller is co-ordinating the different implementations for the Location Service, e.g. E-OTD or GPS. For testing and demonstration purpose SMS-based communication needs to be implemented. This enables E-OTD functionality tests at the CPS test facility side, as there are no RRLP function tests available yet. For instance a new SMS based location request is handled by ACI. ACI forwards the request to the LC controller where a request is passed to RR for starting a single data acquisition request to Layer 1. Layer 1 is performing the acquisition and passing the data over RR back to the LC controller. These data is processed inside the Cursor Algorithm and formatted in one single SMS for distributing to the Test environment over the LC controller and ACI. In case of a real network or RRLP enabled test environment the RRLP module is used instead of the SMS-based approach, the rest of the functionality stays the same

1.3 Cursor module

The Cursor Algorithm is available only in object form where the Cursor Bridge is available in source code and will be adapted to the internal needs. Part of the Cursor Bridge is the SMS formatting module, preparing the processed data inside one SMS for further distribution.

2 LC Controller

2.1 State Machine




Figure 2: The state machine for LC Controller.

The state machine for the Controller is made of three states: IDLE, RRLP_REQUEST and SMS_REQUEST. Figure 2 gives an overview of the state machine and state transitions. Only events causing a state transition are shown in the figure.

IDLE:

IDLE is the initial state. The state handles periodic measurements arriving unsolicited from RR. The RRLP_REQUEST state is entered at reception of an RRLP_POS_IND if there are no measurements already saved in the algorithm. The SMS_REQUEST state is entered at reception of an MNLC_SMS_MEAS_REQ if there are no measurements already saved in the algorithm.

RRLP_REQUEST:

In this state the Controller is waiting for a RRLC_MEAS_IND with the additional measurements from RR. When this arrives the RRLP_POS_RES is send and the Controller returns to IDLE. If instead an error arrives from RR, for instance in case of the serving BTS is different from the reference BTS, the IDLE state is also entered.

SMS_REQUEST:

In this state the Controller is waiting for a RRLC_MEAS_IND with the additional measurements from RR. When this arrives the MNLC_SMS_MEAS_CNF is send and the Controller returns to IDLE. If instead an error arrives from RR the IDLE state is also entered.

2.2 State / event table

State	State Id Number
IDLE	S1
RRLP_REQUEST	S2
SMS_REQUEST	S3

State / Event	S1	S2	S3
RRLP_POS_IND P1: saved meas. P2: no saved meas.	P1: - P2: S2	-	D
RRLC_ERROR_IND	D	S1	S1
RRLC_MEAS_IND	-	S1	S1
MNLC_SMS_MEAS_REQ P1: saved meas. P2: no saved meas.	P1: - P2: S3	D	-

-: No state change.

D: Discard event.


State change; event parameter dependency: PX: X indicating number for parameter dependency.

3 Functionality


The functionality and behaviour of the Controller are in the following sections described through different scenarios with the help of MSCs.

3.1 SMS request

3.1.1 SMS request, no measurement data




3.1.2 SMS request, measurement data stored.




3.2 RRLP request


3.2.1 RRLP request, no measurement data




3.2.2 RRLP request, measurement data stored




3.2.3 RRLP request, serving BTS not reference BTS




3.2.4 RRLP request, location method not supported



3.2.5 RRLP request, handover during measurements



3.3 Periodic measurement



4 CPS Algorithm

Interface between Controller and CPS Algorithm

Procedures:

- CsrUpdateTimings:** This function call is used to update the Algorithm with periodic measurement data (RRLC_MEAS_IND). The CsrUpdateTimings use the input parameter DataBuffer to deliver measurements.
- GetTimingData:** This function call is used to get position data from the Algorithm. The position calculation is received in TimingData. TA data is used as input to the Algorithm if it has been received.
- CreateSMS:** This function is only used for test. The function call is used to generate a SMS message containing the position calculation with a maximum of 140 bytes in a CPS proprietary format. The message is delivered to the ACI layer.
- Global Entity data:
- TaBuffer:** TaBuffer is used when the RRLC_MEAS_IND contains the TA data received in a CS setup. The Controller shall copy the TA data to the TaBuffer, which is used as input for the Algorithm. When the Algorithm use the TA data the position calculation is more precise.
- DataBuffer:** DataBuffer is used when periodic data (RRLC_MEAS_IND) is received, the controller shall copy the signal to the DataBuffer.
- TimingData:** TimingData is used by the Algorithm to deliver position calculations.

Appendices

A. Acronyms

DS-WCDMA Direct Sequence/Spread Wideband Code Division Multiple Access

B. Glossary

International Mobile Telecommunication 2000 (IMT-2000/ITU-2000) Formerly referred to as FPLMTS (Future Public Land-Mobile Telephone System), this is the ITU's specification/family of standards for 3G. This initiative provides a global infrastructure through both satellite and terrestrial systems, for fixed and mobile phone users. The family of standards is a framework comprising a mix/blend of systems providing global roaming. <URL: <http://www.imt-2000.org/>>