



Technical Document - Confidential

GSM PROTOCOL STACK
MESSAGE SEQUENCE CHARTS
SUPPLEMENTARY SERVICES

| | |
|---------------------|-------------------------|
| Document Number: | 6301.209.98.100 |
| Version: | 0.2 |
| Status: | Draft |
| Approval Authority: | |
| Creation Date: | 1998-Aug-07 |
| Last changed: | 2015-Mar-08 by XINTEGRA |
| File Name: | ss.doc |

Important Notice

Texas Instruments Incorporated and/or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and/or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and/or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and/or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and/or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and/or the licensing of software does not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronically or mechanically, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

| Date | Changed by | Approved by | Version | Status | Notes |
|-------------|---------------------|-------------|---------|--------|-------|
| 1998-Aug-07 | Stefan Lemke et al. | | 0.1 | | 1 |
| 2003-Jun-10 | XINTEGRA | | 0.2 | Draft | |

Notes:

1. Initial version

Table of Contents

| | | |
|-------|--|----|
| 1.1 | References | 3 |
| 1.2 | Abbreviations | 7 |
| 1.3 | Terms | 8 |
| 4.1 | Connection Establishment | 11 |
| 4.1.1 | Mobile Originated Connection Establishment | 11 |
| 4.1.2 | Mobile Terminated Connection Establishment | 13 |
| 4.2 | Connected..... | 14 |
| 4.2.1 | Exchange of Facility Messages | 14 |
| 4.3 | Connection Release | 15 |
| 4.3.1 | Call Reestablishment | 15 |
| 4.3.2 | Release by Mobility Management | 16 |
| 4.3.3 | Mobile Originated Connection Release | 17 |
| 4.3.4 | Mobile Terminated Connection Release | 18 |
| A. | Acronyms | 19 |
| B. | Glossary | 19 |

List of Figures and Tables

List of References

- [ISO 9000:2000]** International Organization for Standardization. Quality management systems - Fundamentals and vocabulary. December 2000

1.1 References

- [1] GSM 2.81, Line Identification Supplementary Services - Stage 1
ETS 300 514, ETSI, September 1994
- [2] GSM 2.82, Call Forwarding Supplementary Services - Stage 1
ETS 300 515, ETSI, September 1994
- [3] GSM 2.83, Call Waiting and Call Hold Supplementary Services - Stage 1
ETS 300 516, ETSI, September 1994
- [4] GSM 2.84, Multi Party Supplementary Services - Stage 1
ETS 300 517, ETSI, September 1994
- [5] GSM 2.85, Closed User Group Supplementary Services - Stage 1
ETS 300 518, ETSI, September 1994
- [6] GSM 2.86, Advice of Charge Supplementary Services - Stage 1
ETS 300 519, ETSI, September 1994
- [7] GSM 2.88, Call Barring Supplementary Services - Stage 1
ETS 300 520, ETSI, September 1994
- [8] GSM 3.14, Support of Dual Tone Multi Frequency Signalling via the GSM System
ETS 300 532, ETSI, April 1994

- [9] GSM 3.40, Technical Realization of the Short Message Service Point-to-Point
ETS 300 536, ETSI, January 1996
- [10] GSM 3.41, Technical Realization of Short Message Service Cell Broadcast
ETS 300 537, ETSI, June 1995
- [11] GSM 3.81, Line Identification Supplementary Services - Stage 2
ETS 300 542, ETSI, February 1995
- [12] GSM 3.82, Call Forwarding Supplementary Services - Stage 2
ETS 300 543, ETSI, February 1995
- [13] GSM 3.83, Call Waiting and Call Hold Supplementary Services - Stage 2
ETS 300 544, ETSI, November 1994
- [14] GSM 3.84, Multi Party Supplementary Services - Stage 2
ETS 300 545, ETSI, November 1994
- [15] GSM 3.85, Closed User Group Supplementary Services - Stage 2
ETS 300 546, ETSI, January 1996
- [16] GSM 3.86, Advice of Charge Supplementary Services - Stage 2
ETS 300 547, ETSI, March 1995
- [17] GSM 3.88, Call Barring Supplementary Services - Stage 2
ETS 300 548, ETSI, November 1994
- [18] GSM 4.01, MS-BSS Interface General Aspects and Principles
ETS 300 550, ETSI, September 1994
- [18a] GSM 4.03, MS-BSS Interface Channel Structures and Access Capabilities
ETS 300 552, ETSI, September 1994
- [19] GSM 4.05, Data Link Layer General Aspects
ETS 300 554, ETSI, September 1994
- [20] GSM 4.06, MS-BSS Interface Data Link Layer Specification
ETS 300 555, ETSI, September 1994
- [21] GSM 4.07, Mobile Radio Interface Signalling Layer 3 General Aspects
ETS 300 556, ETSI, February 1995
- [22] GSM 4.08, Mobile Radio Interface Layer 3 Specification
ETS 300 557, ETSI, January 1996
- [23] GSM 4.10, Mobile Radio Interface Layer 3 Supplementary Services Specification
General Aspects
ETS 300 558, ETSI, February 1995
- [24] GSM 4.11, Point-to-Point Short Message Service Support on Mobile Radio Interface
ETS 300 559, ETSI, October 1995
- [25] GSM 4.12, Short Message Service Cell Broadcast Support on Mobile Radio Interface
ETS 300 560, ETSI, January 1996
- [26] GSM 4.80, Mobile Radio Interface Supplementary Services Specification Formats and Coding
ETS 300 564, ETSI, February 1995
- [27] GSM 4.81, Line Identification Supplementary Services - Stage 3
ETS 300 565, ETSI, February 1995
- [28] GSM 4.82, Call Forwarding Supplementary Services - Stage 3
ETS 300 566, ETSI, February 1995
- [29] GSM 4.83, Call Waiting and Call Hold Supplementary Services - Stage 3
ETS 300 567, ETSI, February 1995
- [30] GSM 4.84, Multi Party Supplementary Services - Stage 3
ETS 300 568, ETSI, February 1995

- [31] GSM 4.85, Closed User Group Supplementary Services - Stage 3
ETS 300 569, ETSI, February 1995
- [32] GSM 4.86, Advice of Charge Supplementary Services - Stage 3
ETS 300 570, ETSI, February 1995
- [33] GSM 4.88, Call Barring Supplementary Services - Stage 3
ETS 300 571, ETSI, February 1995
- [34] GSM 5.01, Physical Layer on the Radio Path General Description
ETS 300 573, ETSI, October 1995
- [35] GSM 5.02, Multiplexing and Multiple Access on the Radio Path
ETS 300 574, ETSI, January 1996
- [36] GSM 5.08, Radio Sub-system Link Control
ETS 300 578, ETSI, January 1996
- [37] GSM 5.10, Radio Sub-system Synchronisation
ETS 300 579, ETSI, October 1995
- [38] Service Access Point MMREG
6147.100.96.100; Condat GmbH
- [39] Service Access Point MNCC
6147.101.96.100; Condat GmbH
- [40] Service Access Point MNSS
6147.102.96.100; Condat GmbH
- [41] Service Access Point MNSMS
6147.103.96.100; Condat GmbH
- [42] Service Access Point MMCC
6147.104.97.100; Condat GmbH
- [43] Service Access Point MMSS
6147.105.97.100; Condat GmbH
- [44] Service Access Point MMSMS
6147.106.97.100; Condat GmbH
- [45] Service Access Point RR
6147.107.97.100; Condat GmbH
- [46] Service Access Point SIM
6147.108.97.100; Condat GmbH
- [47] Service Access Point MPH
6147.109.96.100; Condat GmbH
- [48] Service Access Point DL
6147.110.96.100; Condat GmbH
- [49] Service Access Point MDL
6147.111.96.100; Condat GmbH
- [50] Service Access Point PH
6147.112.97.100; Condat GmbH
- [51] Service Access Point MMI
6147.113.96.100; Condat GmbH
- [52] Message Sequence Charts CC
6147.200.97.100; Condat GmbH
- [53] Message Sequence Charts SS
6147.201.97.100; Condat GmbH

- [54] Message Sequence Charts SMS
6147.202.97.100; Condat GmbH
- [55] Message Sequence Charts MM
6147.203.97.100; Condat GmbH
- [56] Message Sequence Charts RR
6147.204.96.100; Condat GmbH
- [57] Message Sequence Charts DL
6147.205.96.100; Condat GmbH
- [58] Users Guide
6147.300.96.100; Condat GmbH
- [59] Test Specification CC
6147.400.97.100; Condat GmbH
- [60] Test Specification SS
6147.401.97.100; Condat GmbH
- [61] Test Specification SMS
6147.402.97.100; Condat GmbH
- [62] Test Specification MM
6147.403.97.100; Condat GmbH
- [63] Test Specification RR
6147.404.97.100; Condat GmbH
- [64] Test Specification DL
6147.405.97.100; Condat GmbH
- [65] Test Specification CCD
6147.406.97.100; Condat GmbH
- [66] SDL Specification CC
6147.500.97.100; Condat GmbH
- [67] SDL Specification SS
6147.501.97.100; Condat GmbH
- [68] SDL Specification SMS
6147.502.97.100; Condat GmbH
- [69] SDL Specification MM
6147.503.97.100; Condat GmbH
- [70] SDL Specification RR
6147.504.97.100; Condat GmbH
- [71] SDL Specification DL
6147.505.97.100; Condat GmbH
- [72] Message Specification CC
6147.600.97.100; Condat GmbH
- [73] Message Specification SS
6147.601.97.100; Condat GmbH
- [74] Message Specification SMS
6147.602.97.100; Condat GmbH
- [75] Message Specification MM
6147.603.97.100; Condat GmbH
- [76] Message Specification RR
6147.604.97.100; Condat GmbH

| | |
|------|---|
| [77] | Message Specification DL 6147.605.97.100; Condat GmbH |
| [78] | Technical Documentation CC 6147.700.97.100; Condat GmbH |
| [79] | Technical Documentation SS 6147.701.97.100; Condat GmbH |
| [80] | Technical Documentation SMS 6147.702.97.100; Condat GmbH |
| [81] | Technical Documentation MM 6147.703.97.100; Condat GmbH |
| [82] | Technical Documentation RR 6147.704.97.100; Condat GmbH |
| [83] | Technical Documentation DL 6147.705.97.100; Condat GmbH |
| [84] | Technical Documentation CCD 6147.706.97.100; Condat GmbH |

1.2 Abbreviations

| | |
|-------|--|
| AGCH | Access Grant Channel |
| BCCH | Broadcast Control Channel |
| BS | Base Station |
| BSIC | Base Station Identification Code |
| CBCH | Cell Broadcast Channel |
| CBQ | Cell Bar Qualify |
| CC | Call Control |
| CCCH | Common Control Channel |
| CCD | Condat Coder Decoder |
| CKSN | Ciphering Key Sequence Number |
| C/R | Command / Response |
| C1 | Path Loss Criterion |
| C2 | Reselection Criterion |
| DCCH | Dedicated Control Channel |
| DISC | Disconnect Frame |
| DL | Data Link Layer |
| DM | Disconnected Mode Frame |
| EA | Extension Bit Address Field |
| EL | Extension Bit Length Field |
| EMMI | Electrical Man Machine Interface |
| F | Final Bit |
| FACCH | Fast Associated Control Channel |
| FHO | Forced Handover |
| GP | Guard Period |
| GSM | Global System for Mobile Communication |
| HPLMN | Home Public Land Mobile Network |
| I | Information Frame |
| IMEI | International Mobile Equipment Identity |
| IMSI | International Mobile Subscriber Identity |
| Kc | Authentication Key |
| L | Length Indicator |
| LAI | Location Area Information |
| LPD | Link Protocol Discriminator |
| M | More Data Bit |
| MCC | Mobile Country Code |

| | |
|-------|--------------------------------------|
| MM | Mobility Management |
| MMI | Man Machine Interface |
| MNC | Mobile Network Code |
| MS | Mobile Station |
| NCC | National Colour Code |
| NECI | New Establishment Causes included |
| N(R) | Receive Number |
| N(S) | Send Number |
| OTD | Observed Time Difference |
| P | Poll Bit |
| PCH | Paging Channel |
| PDU | Protocol Description Unit |
| P/F | Poll / Final Bit |
| PL | Physical Layer |
| PLMN | Public Land Mobile Network |
| RACH | Random Access Channel |
| REJ | Reject Frame |
| RNR | Receive Not Ready Frame |
| RR | Radio Resource Management |
| RR | Receive Ready Frame |
| RTD | Real Time Difference |
| SABM | Set Asynchronous Balanced Mode |
| SACCH | Slow Associated Control Channel |
| SAP | Service Access Point |
| SAPI | Service Access Point Identifier |
| SDCCH | Slow Dedicated Control Channel |
| SIM | Subscriber Identity Module |
| SMS | Short Message Service |
| SMSCB | Short Message Service Cell Broadcast |
| SS | Supplementary Services |
| TCH | Traffic Channel |
| TCH/F | Traffic Channel Full Rate |
| TCH/H | Traffic Channel Half Rate |
| TDMA | Time Division Multiple Access |
| TMSI | Temporary Mobile Subscriber Identity |
| UA | Unnumbered Acknowledgement Frame |
| UI | Unnumbered Information Frame |
| VPLMN | Visiting Public Land Mobile Network |
| V(A) | Acknowledgement State Variable |
| V(R) | Receive State Variable |
| V(S) | Send State Variable |

1.3 Terms

| | |
|----------------------|--|
| Entity: | Program which executes the functions of a layer |
| Message: | A message is a data unit which is transferred between the entities of the same layer (peer-to-peer) of the mobile and infrastructure side. Message is used as a synonym to protocol data unit (PDU). A message may contain several information elements. |
| Primitive: | A primitive is a data unit which is transferred between layers on one component (mobile station or infrastructure). The primitive has an operation code which identifies the primitive and its parameters. |
| Service Access Point | A Service Access Point is a data interface between two layers on one component (mobile station or infrastructure). |

2 Overview

The Protocol Stacks are used to define the functionality of the GSM protocols for interfaces. The GSM specifications are normative when used to describe the functionality of interfaces, but the stacks and the subdivision of protocol layers does not imply or restrict any implementation.

The base of the Protocol Stack rests on the physical layer.

The Data Link Layer (DL) is used to handle an acknowledged connection between mobile and base station. The LAPDm protocol is used.

Radio Resource (RR) manages the resources of the air-interface. That means configuration of physical layer, cell selection and cell reselection, data transfer, RR-Connection handling.

Mobility Management (MM) handles registration aspects for the mobile station. It detects changes of location areas and updates a mobile station in the new location area.

Call Control (CC) provides the call functionality. This includes call establishment, call maintenance procedures like Hold, Retrieve or Modify, and call disconnection.

Supplementary Services (SS) handles all call independent supplementary services like call forwarding or call barring.

Short Message Services (SMS) is used for sending and receiving point-to-point short messages. Additionally the reception of cell broadcast short messages is included.

The man machine interface (MMI) is the interface to the user. Normally it is connected with a keypad as input device and a display as output device.


Between the several entities data interfaces are defined. These data interfaces are called Service Access Points (SAPs), indicating that an upper layer uses the services of a lower layer.

The SIM card used by MM, MMI and SMS in several ways. This document describes the services needed for the SIM application.

4 Procedures

4.1 Connection Establishment

4.1.1 Mobile Originated Connection Establishment



(SS 1)

MMI starts establishment of a connection. A facility information element and the SS version info are forwarded to SS. SS checks the transaction identifier. It is not expected that this leads to a problem, because the MS shall make no internal errors. If this check fails, the request is ignored.

(MM 1)

SS stores the facility and the SS version information element and requests a MM connection by MM. The new state of SS is MM CONNECTION PENDING. In this state SS awaits the confirmation for the MM connection.

(SS 2)

MM has established a MM connection successfully and confirms this to SS.

(MM 2)

Using the stored information elements for facility and SS version, SS codes a SS REGISTER message and sends this message to the infrastructure. Any SS transaction starts with the SS REGISTER message. SS enters the state CONNECTED.


(SS 3)

MM was not able to establish a MM connection. This is signalled to SS.

(MMI 1)

MMI is informed about the release.

4.1.2 Mobile Terminated Connection Establishment



(SS 1)

SS receives a message. It must be a SS REGISTER message, because it is the first message of this transaction.

(MMI 1)


SS checks the message type and the transaction identifier. If it is a SS REGISTER message and the transaction identifier is not reserved and in the range for mobile terminated transactions, SS forwards the content (facility information) to MMI.

(MM 1)

If this check fails, SS ignores the message and releases the connection. MM is informed about this.

4.3 Connection Release

4.3.1 Call Reestablishment



(SS 1)

MM indicates an error in the lower layer with the possibility to reestablishment in the cell.


(MMI 1)

SS will not process reestablishment in general. MMI is informed about the end of the transaction.

(MM 1)

MM is informed about the end of transaction.

4.3.2 Release by Mobility Management




(SS 1)

MM indicates the connection release.

(MMI 1)

MMI is informed about the end of transaction.

4.3.4 Mobile Terminated Connection Release



(SS 1)

The infrastructure will release the transaction. The last message of a SS transaction is the SS RELEASE COMPLETE message.

(MM 1)

SS decodes the message and forwards the content to MMI.

(MM 2)

MM is informed about the end of transaction.

Appendices

A. Acronyms

DS-WCDMA Direct Sequence/Spread Wideband Code Division Multiple Access

B. Glossary

International Mobile Telecommunication 2000 (IMT-2000/ITU-2000) Formerly referred to as FPLMTS (Future Public Land-Mobile Telephone System), this is the ITU's specification/family of standards for 3G. This initiative provides a global infrastructure through both satellite and terrestrial systems, for fixed and mobile phone users. The family of standards is a framework comprising a mix/blend of systems providing global roaming. <URL: <http://www.imt-2000.org/>>