



Technical Document - Confidential

GSM PROTOCOL STACK

TEST SPECIFICATION

BMI (PART A)

Document Number:	xxxx.yyy.00.100
Version:	0.2
Status:	Draft
Approval Authority:	
Creation Date:	1998-Nov-10
Last changed:	2015-Mar-08 by XGUTTEFE
File Name:	bmia.doc

Important Notice

Texas Instruments Incorporated and/or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and/or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and/or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and/or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and/or software may be based on or implement industry recognized standards and that certain third parties may claim intellectual property rights therein. The supply of products and/or the licensing of software does not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronically or mechanically, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

Date	Changed by	Approved by	Version	Status	Notes
1998-Nov-10	LE, ES, VO		0.1		1
2003-May-12	XGUTTEFE		0.2	Draft	

Notes:

1. Initial version

Table of Contents

1.1	References	5
1.2	Abbreviations	8
1.3	Terms	10
2	Overview	11
3	Parameters	13
4	TEST CASES	15
4.1	Routing (internal)	15
4.1.1	BMIA001: Setup the Routing and the PCO view for the MMI test	15
4.2	MMI Component Tests	16
4.2.1	BMIA200: Power On Sequence	16
4.2.2	BMIA201: Power On Sequence with PIN entering	18
4.2.3	BMIA202: Power On Sequence, limited service	20
4.2.4	BMIA203: Power On Sequence, no service	21
4.2.5	BMIA204: Power On Sequence, No SIM card, limited service	23
4.2.6	BMIA205: Power On Sequence, No SIM card, no service	24
4.2.7	BMIA206: Power On Sequence, Invalid SIM card, limited service	24
4.2.8	BMIA207: Power On Sequence, Invalid SIM card, no service	26
4.2.9	BMIA208: Power On Sequence, Blocked SIM card	26
4.2.10	BMIA210: Power On Sequence with PIN entering, initial testcase	28
4.2.11	BMIA211: Power On Sequence with PIN entering, enter digits, successfull	29
4.2.12	BMIA212: Power On Sequence with PIN entering, enter digits and clear	31
4.2.13	BMIA213: Power On Sequence with PIN entering, enter digits and clear II	33
4.2.14	BMIA214: Power On Sequence with PIN entering, clear if nothing to clear	34
4.2.15	BMIA215: Power On Sequence with PIN entering, exact eight digits	36
4.2.16	BMIA216: Power On Sequence with PIN entering, exact eight digits with clearing	38
4.2.17	BMIA217: Power On Sequence with PIN entering, more then eight digits	40
4.2.18	BMIA218: Power On Sequence with PIN entering, okay after three digits	42
4.2.19	BMIA219: Power On Sequence with PIN entering, wrong keys used	43
4.2.20	BMIA220: Power On Sequence with PIN entering, failure on verification	44
4.2.21	BMIA221: Power On Sequence with PIN entering, general failure - testcase don't run	46
4.2.22	BMIA222: Power On Sequence with PIN entering, repeated failures on verification	47
4.2.23	BMIA223: Power On Sequence, PUK verification, successful case, without registration (missing in bmi_regi: SimManEH)	50
4.2.24	BMIA224: Power On Sequence, PUK verification, new PIN is different, switch off	51
4.2.25	BMIA225: Power On Sequence, PUK verification, PUK is wrong	53
4.2.26	BMIA226: Power On Sequence, PUK verification, long pressed clear	57
4.2.27	BMIA227: Power On Sequence, PUK verification, new PIN, long pressed clear	60
4.2.28	BMIA228: Power On Sequence, Invalid Sim Card, start Emergency call	62
Appendices		64
A.	Acronyms	64
B.	Glossary	64

List of Figures and Tables

List of References

- [ISO 9000:2000]** International Organization for Standardization. Quality management systems - Fundamentals and vocabulary. December 2000

1.1 References

- [1] GSM 2.81, Line Identification Supplementary Services - Stage 1
ETS 300 514, ETSI, September 1994
- [2] GSM 2.82, Call Forwarding Supplementary Services - Stage 1
ETS 300 515, ETSI, September 1994
- [3] GSM 2.83, Call Waiting and Call Hold Supplementary Services - Stage 1
ETS 300 516, ETSI, September 1994
- [4] GSM 2.84, Multi Party Supplementary Services - Stage 1
ETS 300 517, ETSI, September 1994
- [5] GSM 2.85, Closed User Group Supplementary Services - Stage 1
ETS 300 518, ETSI, September 1994
- [6] GSM 2.86, Advice of Charge Supplementary Services - Stage 1
ETS 300 519, ETSI, September 1994
- [7] GSM 2.88, Call Barring Supplementary Services - Stage 1
ETS 300 520, ETSI, September 1994
- [8] GSM 3.14, Support of Dual Tone Multi Frequency Signalling via the GSM System
ETS 300 532, ETSI, April 1994
- [9] GSM 3.40, Technical Realization of the Short Message Service Point-to-Point
ETS 300 536, ETSI, January 1996
- [10] GSM 3.41, Technical Realization of Short Message Service Cell Broadcast
ETS 300 537, ETSI, June 1995
- [11] GSM 3.81, Line Identification Supplementary Services - Stage 2
ETS 300 542, ETSI, February 1995
- [12] GSM 3.82, Call Forwarding Supplementary Services - Stage 2
ETS 300 543, ETSI, February 1995
- [13] GSM 3.83, Call Waiting and Call Hold Supplementary Services - Stage 2
ETS 300 544, ETSI, November 1994
- [14] GSM 3.84, Multi Party Supplementary Services - Stage 2
ETS 300 545, ETSI, November 1994
- [15] GSM 3.85, Closed User Group Supplementary Services - Stage 2
ETS 300 546, ETSI, January 1996
- [16] GSM 3.86, Advice of Charge Supplementary Services - Stage 2
ETS 300 547, ETSI, March 1995
- [17] GSM 3.88, Call Barring Supplementary Services - Stage 2
ETS 300 548, ETSI, November 1994
- [18] GSM 4.01, MS-BSS Interface General Aspects and Principles
ETS 300 550, ETSI, September 1994
- [18a] GSM 4.03, MS-BSS Interface Channel Structures and Access Capabilities
ETS 300 552, ETSI, September 1994
- [19] GSM 4.05, Data Link Layer General Aspects
ETS 300 554, ETSI, September 1994
- [20] GSM 4.06, MS-BSS Interface Data Link Layer Specification
ETS 300 555, ETSI, September 1994
- [21] GSM 4.07, Mobile Radio Interface Signalling Layer 3 General Aspects
ETS 300 556, ETSI, February 1995

- [22] GSM 4.08, Mobile Radio Interface Layer 3 Specification
ETS 300 557, ETSI, January 1996
- [23] GSM 4.10, Mobile Radio Interface Layer 3 Supplementary Services Specification
General Aspects
ETS 300 558, ETSI, February 1995
- [24] GSM 4.11, Point-to-Point Short Message Service Support on Mobile Radio Interface
ETS 300 559, ETSI, October 1995
- [25] GSM 4.12, Short Message Service Cell Broadcast Support on Mobile Radio Interface
ETS 300 560, ETSI, January 1996
- [26] GSM 4.80, Mobile Radio Interface Supplementary Services Specification Formats and Coding
ETS 300 564, ETSI, February 1995
- [27] GSM 4.81, Line Identification Supplementary Services - Stage 3
ETS 300 565, ETSI, February 1995
- [28] GSM 4.82, Call Forwarding Supplementary Services - Stage 3
ETS 300 566, ETSI, February 1995
- [29] GSM 4.83, Call Waiting and Call Hold Supplementary Services - Stage 3
ETS 300 567, ETSI, February 1995
- [30] GSM 4.84, Multi Party Supplementary Services - Stage 3
ETS 300 568, ETSI, February 1995
- [31] GSM 4.85, Closed User Group Supplementary Services - Stage 3
ETS 300 569, ETSI, February 1995
- [32] GSM 4.86, Advice of Charge Supplementary Services - Stage 3
ETS 300 570, ETSI, February 1995
- [33] GSM 4.88, Call Barring Supplementary Services - Stage 3
ETS 300 571, ETSI, February 1995
- [34] GSM 5.01, Physical Layer on the Radio Path General Description
ETS 300 573, ETSI, October 1995
- [35] GSM 5.02, Multiplexing and Multiple Access on the Radio Path
ETS 300 574, ETSI, January 1996
- [36] GSM 5.08, Radio Sub-system Link Control
ETS 300 578, ETSI, January 1996
- [37] GSM 5.10, Radio Sub-system Synchronisation
ETS 300 579, ETSI, October 1995
- [38] Service Access Point MMREG
6147.100.96.100; Condat GmbH
- [39] Service Access Point MNCC
6147.101.96.100; Condat GmbH
- [40] Service Access Point MNSS
6147.102.96.100; Condat GmbH
- [41] Service Access Point MNSMS
6147.103.96.100; Condat GmbH
- [42] Service Access Point MMCC
6147.104.97.100; Condat GmbH
- [43] Service Access Point MMSS
6147.105.97.100; Condat GmbH
- [44] Service Access Point MMSMS
6147.106.97.100; Condat GmbH

[45]	Service Access Point RR 6147.107.97.100; Condat GmbH
[46]	Service Access Point SIM 6147.108.97.100; Condat GmbH
[47]	Service Access Point MPH 6147.109.96.100; Condat GmbH
[48]	Service Access Point DL 6147.110.96.100; Condat GmbH
[49]	Service Access Point MDL 6147.111.96.100; Condat GmbH
[50]	Service Access Point PH 6147.112.97.100; Condat GmbH
[51]	Service Access Point MMI 6147.113.96.100; Condat GmbH
[52]	Message Sequence Charts CC 6147.200.97.100; Condat GmbH
[53]	Message Sequence Charts SS 6147.201.97.100; Condat GmbH
[54]	Message Sequence Charts SMS 6147.202.97.100; Condat GmbH
[55]	Message Sequence Charts MM 6147.203.97.100; Condat GmbH
[56]	Message Sequence Charts RR 6147.204.96.100; Condat GmbH
[57]	Message Sequence Charts DL 6147.205.96.100; Condat GmbH
[58]	Users Guide 6147.300.96.100; Condat GmbH
[59]	Test Specification CC 6147.400.97.100; Condat GmbH
[60]	Test Specification SS 6147.401.97.100; Condat GmbH
[61]	Test Specification SMS 6147.402.97.100; Condat GmbH
[62]	Test Specification MM 6147.403.97.100; Condat GmbH
[63]	Test Specification RR 6147.404.97.100; Condat GmbH
[64]	Test Specification DL 6147.405.97.100; Condat GmbH
[65]	Test Specification CCD 6147.406.97.100; Condat GmbH
[66]	SDL Specification CC 6147.500.97.100; Condat GmbH
[67]	SDL Specification SS 6147.501.97.100; Condat GmbH

[68]	SDL Specification SMS 6147.502.97.100; Condat GmbH
[69]	SDL Specification MM 6147.503.97.100; Condat GmbH
[70]	SDL Specification RR 6147.504.97.100; Condat GmbH
[71]	SDL Specification DL 6147.505.97.100; Condat GmbH
[72]	Message Specification CC 6147.600.97.100; Condat GmbH
[73]	Message Specification SS 6147.601.97.100; Condat GmbH
[74]	Message Specification SMS 6147.602.97.100; Condat GmbH
[75]	Message Specification MM 6147.603.97.100; Condat GmbH
[76]	Message Specification RR 6147.604.97.100; Condat GmbH
[77]	Message Specification DL 6147.605.97.100; Condat GmbH
[78]	Technical Documentation CC 6147.700.97.100; Condat GmbH
[79]	Technical Documentation SS 6147.701.97.100; Condat GmbH
[80]	Technical Documentation SMS 6147.702.97.100; Condat GmbH
[81]	Technical Documentation MM 6147.703.97.100; Condat GmbH
[82]	Technical Documentation RR 6147.704.97.100; Condat GmbH
[83]	Technical Documentation DL 6147.705.97.100; Condat GmbH
[84]	Technical Documentation CCD 6147.706.97.100; Condat GmbH

1.2 Abbreviations

AGCH	Access Grant Channel
BCCH	Broadcast Control Channel
BS	Base Station
BSIC	Base Station Identification Code
CBCH	Cell Broadcast Channel
CBQ	Cell Bar Qualify
CC	Call Control
CCCH	Common Control Channel
CCD	Condat Coder Decoder
CKSN	Ciphering Key Sequence Number
C/R	Command / Response

C1	Path Loss Criterion
C2	Reselection Criterion
DCCH	Dedicated Control Channel
DISC	Disconnect Frame
DL	Data Link Layer
DM	Disconnected Mode Frame
EA	Extension Bit Address Field
EL	Extension Bit Length Field
EMMI	Electrical Man Machine Interface
F	Final Bit
FACCH	Fast Associated Control Channel
FHO	Forced Handover
GP	Guard Period
GSM	Global System for Mobile Communication
HPLMN	Home Public Land Mobile Network
I	Information Frame
IMEI	International Mobile Equipment Identity
IMSI	International Mobile Subscriber Identity
Kc	Authentication Key
L	Length Indicator
LAI	Location Area Information
LPD	Link Protocol Discriminator
M	More Data Bit
MCC	Mobile Country Code
MM	Mobility Management
MMI	Man Machine Interface
MNC	Mobile Network Code
MS	Mobile Station
NCC	National Colour Code
NECI	New Establishment Causes included
N(R)	Receive Number
N(S)	Send Number
OTD	Observed Time Difference
P	Poll Bit
PCH	Paging Channel
PDU	Protocol Description Unit
P/F	Poll / Final Bit
PL	Physical Layer
PLMN	Public Land Mobile Network
RACH	Random Access Channel
REJ	Reject Frame
RNR	Receive Not Ready Frame
RR	Radio Resource Management
RR	Receive Ready Frame
RTD	Real Time Difference
SABM	Set Asynchronous Balanced Mode
SACCH	Slow Associated Control Channel
SAP	Service Access Point
SAPI	Service Access Point Identifier
SDCCH	Slow Dedicated Control Channel
SIM	Subscriber Identity Module
SMS	Short Message Service
SMSCB	Short Message Service Cell Broadcast
SS	Supplementary Services
TCH	Traffic Channel
TCH/F	Traffic Channel Full Rate
TCH/H	Traffic Channel Half Rate
TDMA	Time Division Multiple Access
TMSI	Temporary Mobile Subscriber Identity

UA	Unnumbered Acknowledgement Frame
UI	Unnumbered Information Frame
VPLMN	Visiting Public Land Mobile Network
V(A)	Acknowledgement State Variable
V(R)	Receive State Variable
V(S)	Send State Variable

1.3 Terms

Entity:	Program which executes the functions of a layer
Message:	A message is a data unit which is transferred between the entities of the same layer (peer-to-peer) of the mobile and infrastructure side. Message is used as a synonym to protocol data unit (PDU). A message may contain several information elements.
Primitive:	A primitive is a data unit which is transferred between layers on one component (mobile station or infrastructure). The primitive has an operation code which identifies the primitive and its parameters.
Service Access Point	A Service Access Point is a data interface between two layers on one component (mobile station or infrastructure).

2 Overview

The Protocol Stacks are used to define the functionality of the GSM protocols for interfaces. The GSM specifications are normative when used to describe the functionality of interfaces, but the stacks and the subdivision of protocol layers does not imply or restrict any implementation.

The base of the Protocol Stack rests on the physical layer.

The Data Link Layer (DL) is used to handle an acknowledged connection between mobile and base station. The LAPDm protocol is used.

Radio Resource (RR) manages the resources of the air-interface. That means configuration of physical layer, cell selection and cell reselection, data transfer, RR-Connection handling.

Mobility Management (MM) handles registration aspects for the mobile station. It detects changes of location areas and updates a mobile station in the new location area.

Call Control (CC) provides the call functionality. This includes call establishment, call maintenance procedures like Hold, Retrieve or Modify, and call disconnection.

Supplementary Services (SS) handles all call independent supplementary services like call forwarding or call barring.

Short Message Services (SMS) is used for sending and receiving point-to-point short messages. Additionally the reception of cell broadcast short messages is included.

The man machine interface (MMI) is the interface to the user. Normally it is connected with a keypad as input device and a display as output device.

Between the several entities data interfaces are defined. These data interfaces are called Service Access Points (SAPs), indicating that an upper layer uses the services of a lower layer.

The GSM specification do not set out any implementation of the Protocol Stack. The following diagrams show the implementation described in all these documents for the mobile station. All entities except the Man Machine Interface and Physical Layer are implemented as part of the Protocol Stack.

Error! Objects cannot be created from editing field codes.

Figure 1: Mobile-station protocol architecture

This document describes the tests for the whole protocol stack using the MMI Framework.

3 Parameters

```
#define PHASE_2_PIN_ENTERING 2
```

```
DECLARATION (PLMN_262_01)
DECLARATION (PLMN_262_02)
DECLARATION (PLMN_262_03)
DECLARATION (PLMN_NO_ID)
DECLARATION (MCC_NONE)
DECLARATION (MNC_NONE)
DECLARATION (MCC_262)
DECLARATION (MCC_765)
DECLARATION (MNC_01)
DECLARATION (MNC_02)
DECLARATION (MNC_03)
DECLARATION (IMSI)
```

```
#define PIN_1          1
#define PIN_2          2
#define PUK_1          3
#define PUK_2          4
```

```
BYTE TI_MO_0      0x00
BYTE NUM_0 0
BYTE NUM_1 1
BYTE NUM_2 2
BYTE NUM_3 3
BYTE NUM_9 9
BYTE NUM_10 10
BYTE V_PLMN_PRE 1
BYTE V_PLMN_NOT_PRE 0
FIELD (PREF_PLMN)
```

```
0x32, 0xF8, 0x10,
0x32, 0xF8, 0x20,
0x02, 0xF8, 0x10,
0x02, 0xF8, 0x01,
0xFF, 0xFF, 0xFF,
0xFF, 0xFF, 0xFF,
0xFF, 0xFF, 0xFF,
0xFF, 0xFF, 0xFF,
0xFF, 0xFF, 0xFF,
0xFF, 0xFF, 0xFF
```

```
ENDFIELD (PREF_PLMN, 30)
```

```
FIELD (PIN_1_VALUE)
```

```
0x31,0x32,0x33,0x34,0xFF,0xFF, 0xFF,0xFF
```

```
ENDFIELD (PIN_1_VALUE, 8)
```

```
FIELD (PIN_1_VALUE_B)
```

```
0x31,0x31,0x32,0x34,0xFF,0xFF, 0xFF,0xFF
```

```
ENDFIELD (PIN_1_VALUE_B, 8)
```

```
FIELD (PIN_1_VALUE_C)
```

```
0x31,0x31,0x31,0x31,0xFF,0xFF, 0xFF,0xFF
```

```
ENDFIELD (PIN_1_VALUE_C, 8)
```

```
FIELD (PIN_1_VALUE_D)
```

```
0x31,0x32,0x33,0x34,0x35, 0x36, 0x37,0x38
```

```

ENDFIELD (PIN_1_VALUE_D, 8)
FIELD (PIN_1_VALUE_E)
                                0x31,0x32,0x33,0x35,0x36, 0x37,0x38,0x39

ENDFIELD (PIN_1_VALUE_E, 8)
FIELD (PIN_1_VALUE_F)
                                0x31,0x32,0x33,0x33,0xFF, 0xFF,0xFF,0xFF

ENDFIELD (PIN_1_VALUE_F, 8)
FIELD (PIN_1_VALUE_G)
                                0x31,0x32,0x33,0xFF,0xFF, 0xFF,0xFF,0xFF

ENDFIELD (PIN_1_VALUE_G, 8)
FIELD (PUK_1_VALUE)
                                0x31,0x32,0x33,0x34,0x35,0x36, 0x37,0x38

ENDFIELD (PUK_1_VALUE, 8)

FIELD (EC_CODES) 0x11, 0xF2, 0xFF,
                  0x99, 0xF9, 0xFF,
                  0xFF, 0xFF, 0xFF,
                  0xFF, 0xFF, 0xFF,
                  0xFF, 0xFF, 0xFF
ENDFIELD (EC_CODES, 15)

/* SIM service table */
FIELD (F_SIM_SRV) 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00
ENDFIELD (F_SIM_SRV, 10)
BEGINARRAY (MCC_262, 3) 0x02, 0x06, 0x02 ENDARRAY
BEGINARRAY (MCC_765, 3) 0x07, 0x06, 0x05 ENDARRAY
BEGINARRAY (MNC_01, 2) 0x00, 0x01 ENDARRAY
BEGINARRAY (MNC_02, 2) 0x00, 0x02 ENDARRAY
BEGINARRAY (MNC_03, 2) 0x00, 0x03 ENDARRAY
BEGINARRAY (MCC_NONE, 3) 0x0F, 0x0F, 0x0F ENDARRAY
BEGINARRAY (MNC_NONE, 3) 0x0F, 0x0F, 0x0F ENDARRAY
BEGINARRAY (IMSI, 9) 0x08, 0x19, 0x32, 0x33, 0x74, 0x11, 0x94, 0x21, 0xFF ENDARRAY

BEGIN_PSTRUCT ("plmn", PLMN_262_01)
    SET_COMP ("v_plmn", V_PLMN_PRE)
    SET_COMP ("mcc", MCC_262)
    SET_COMP ("mnc", MNC_01)
ENDSTRUCT
BEGIN_PSTRUCT ("plmn", PLMN_262_02)
    SET_COMP ("v_plmn", V_PLMN_PRE)
    SET_COMP ("mcc", MCC_262)
    SET_COMP ("mnc", MNC_02)
ENDSTRUCT
BEGIN_PSTRUCT ("plmn", PLMN_262_03)
    SET_COMP ("v_plmn", V_PLMN_PRE)
    SET_COMP ("mcc", MCC_262)
    SET_COMP ("mnc", MNC_03)
ENDSTRUCT
BEGIN_PSTRUCT ("plmn", PLMN_NO_ID)
    SET_COMP ("v_plmn", V_PLMN_NOT_PRE)
    SET_COMP ("mcc", MCC_NONE)
    SET_COMP ("mnc", MNC_NONE)
ENDSTRUCT

```

4 TEST CASES

4.1 Routing (internal)

4.1.1 BMIA001: Setup the Routing and the PCO view for the MMI test

Description:

Routings for the ACI tests are set.

Preamble:

None

APL	ACI	PS
COMMAND (TAP RESET)		
COMMAND (CC RESET)		
COMMAND (MM RESET)		
COMMAND (SIM RESET)		
COMMAND (SS RESET)		
COMMAND (MMI RESET)		
COMMAND (SMS RESET)		
COMMAND (RA RESET)		
COMMAND (T30 RESET)		
COMMAND (TAP REDIRECT CLEAR)		
COMMAND (CC REDIRECT CLEAR)		
COMMAND (MM REDIRECT CLEAR)		
COMMAND (SIM REDIRECT CLEAR)		
COMMAND (SS REDIRECT CLEAR)		
COMMAND (MMI REDIRECT CLEAR)		
COMMAND (SMS REDIRECT CLEAR)		
COMMAND (RA REDIRECT CLEAR)		
COMMAND (T30 REDIRECT CLEAR)		
COMMAND (MMI REDIRECT CC TAP)		
COMMAND (MMI REDIRECT MM TAP)		
COMMAND (MMI REDIRECT SIM TAP)		
COMMAND (MMI REDIRECT SS TAP)		
COMMAND (MMI REDIRECT MMI TAP)		
COMMAND (MMI REDIRECT SMS TAP)		
COMMAND (MMI REDIRECT RA TAP)		
COMMAND (MMI REDIRECT T30 TAP)		
COMMAND (TAP REDIRECT TAP MMI)		
COMMAND (MMI REDIRECT MMI TAP)		
COMMAND (CST REDIRECT L1 TAP)		

Parametrization:

Primitive	Parameter	Value
-----------	-----------	-------

History:	14.12.98	AKInitial
----------	----------	-----------

4.2 MMI Component Tests

4.2.1 BMIA200: Power On Sequence

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	
	<=====	
(8)	MMR_PLMN_MODE_REQ	
	=====>	
(9)	MMR_REG_REQ	
	=====>	
(10)	MMR_REG_CNF	
	<=====	
(11)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc	SIM_INITIALISATION
	mmi_pro_file	NOT_USED
	stk_pro_file	NOT_USED
(2) SIM_ACTIVATE_CNF	error	SIM_INIT_NO_ERROR
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
	ec_code	EC_CODES
	pref_lang	NOT_USED
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED

	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF		
	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF		
	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(8) MMR_PLMN_MODE_REQ		
	mode	MODE_AUTO
(9) MMR_REG_REQ		
	service_mode	SERVICE_MODE_FULL
(10) MMR_REG_CNF		
	plmn	PLMN_262_01
(11) MMR_PLMN_MODE_REQ		
	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.2 BMIA201: Power On Sequence with PIN entering

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	
	<=====	
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(8)	SIM_VERIFY_PIN_REQ	
	=====>	
(9)	SIM_VERIFY_PIN_CNF	
	<=====	
(10)	MMR_PLMN_MODE_REQ	
	=====>	
(11)	MMR_REG_REQ	
	=====>	
(12)	MMR_REG_CNF	
	<=====	
(13)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ		
proc	SIM_INITIALISATION	
mmi_pro_file	NOT_USED	
stk_pro_file	NOT_USED	
(2) SIM_ACTIVATE_CNF		
error	SIM_INVALID_PIN_1	
pin_cnt	NUM_3	
puk_cnt	NUM_10	
pin2_cnt	NUM_3	
puk2_cnt	NUM_10	

ec_code	NOT_USED
pref_lang	NOT_USED
(3) SIM_MMI_INSERT_IND	
func	SIM_ADN_ENABLED
sim_serv	F_SIM_SRV
imsi_field	NOT_USED
pref_plmn	NOT_USED
phase	PHASE_2_SIM
access_acm	NOT_USED
access_acmmmax	NOT_USED
access_puct	NOT_USED
(4) SIM_READ_REQ	
source	SRC_MMI
offset	NOT_USED
datafield	SIM_CPHS_CINF
length	NOT_PRESENT_8BIT
max_length	NOT_USED
(5) SIM_READ_CNF	
datafield	SIM_CPHS_CINF
error	SIM_NO_ERROR
length	NOT_USED
trans_data	NOT_USED
(6) SIM_READ_REQ	
source	SRC_MMI
offset	NOT_USED
datafield	SIM_ECC
length	NOT_PRESENT_8BIT
max_length	NOT_USED
(7) SIM_READ_CNF	
datafield	SIM_ECC
error	SIM_NO_ERROR
length	NOT_USED
trans_data	NOT_USED
(8) SIM_VERIFY_PIN_REQ	
source	SRC_MMI
pin	PIN_1_VALUE
pin_id	PIN_1
(9) SIM_VERIFY_PIN_CNF	
error	SIM_NO_ERROR
pin_id	PIN_1
pin_cnt	NUM_3
puk_cnt	NUM_10
pin2_cnt	NUM_3
puk2_cnt	NUM_10
(10) MMR_PLMN_MODE_REQ	
mode	MODE_AUTO
(11) MMR_REG_REQ	
service_mode	SERVICE_MODE_FULL
(12) MMR_REG_CNF	
plmn	PLMN_262_01
(13) MMR_PLMN_MODE_REQ	
mode	MODE_AUTO

History: 10.08.98

ACI

Initial

4.2.3 BMIA202: Power On Sequence, limited service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	
	<=====	
(8)	MMR_PLMN_MODE_REQ	
	=====>	
(9)	MMR_REG_REQ	
	=====>	
(10)	MMR_NREG_IND	
	<=====	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc	SIM_INITIALISATION
	mmi_pro_file	NOT_USED
	stk_pro_file	NOT_USED
(2) SIM_ACTIVATE_CNF	error	SIM_INIT_NO_ERROR
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
	ec_code	NOT_USED
	pref_lang	NOT_USED
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF

	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF		
	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF		
	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(8) MMR_PLMN_MODE_REQ		
	mode	MODE_AUTO
(9) MMR_REG_REQ		
	service_mode	SERVICE_MODE_FULL
(10) MMR_NREG_IND		
	nreg_cs	NREG_LIMITED_SERVICE
	search_running	SEARCH_NOT_RUNNING
	new_forb_plmn	PLMN_NO_ID
	limited_cause	MMR_RC_NONE
History:	10.08.98	ACI Initial

4.2.4 BMIA203: Power On Sequence, no service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	
	<=====	
(8)	MMR_PLMN_MODE_REQ	
	=====>	
(9)	MMR_REG_REQ	
	=====>	
(10)	MMR_NREG_IND	

| * <=====*

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc	SIM_INITIALISATION
	mmi_pro_file	NOT_USED
	stk_pro_file	NOT_USED
(2) SIM_ACTIVATE_CNF	error	SIM_INIT_NO_ERROR
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
	ec_code	NOT_USED
	pref_lang	NOT_USED
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(8) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(9) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL

(10) MMR_NREG_IND

nreg_cs	NREG_NO_SERVICE
search_running	SEARCH_NOT_RUNNING
new_forb_plmn	PLMN_NO_ID
limited_cause	MMR_RC_NONE

History:	10.08.98	ACI Initial
----------	----------	-------------

4.2.5 BMIA204: Power On Sequence, No SIM card, limited service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	*=====> *	
(2)	SIM_ACTIVATE_CNF	
	*<===== *	
(3)	MMR_PLMN_MODE_REQ	
	*=====> *	
(4)	MMR_REG_REQ	
	*=====> *	
(5)	MMR_NREG_IND	
	*<===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc	SIM_INITIALISATION
	mmi_pro_file	NOT_USED
	stk_pro_file	NOT_USED
(2) SIM_ACTIVATE_CNF	error	SIM_FATAL_ERROR
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
	ec_code	NOT_USED
	pref_lang	NOT_USED
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_NREG_IND	nreg_cs	NREG_NO_SERVICE
	search_running	SEARCH_NOT_RUNNING
	new_forb_plmn	PLMN_NO_ID
	limited_cause	MMR_RC_NONE
History:	10.08.98	ACI Initial

4.2.6 BMIA205: Power On Sequence, No SIM card, no service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_NREG_IND	
	<=====	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc mmi_pro_file stk_pro_file	SIM_INITIALISATION NOT_USED NOT_USED
(2) SIM_ACTIVATE_CNF	error pin_cnt puk_cnt pin2_cnt puk2_cnt ec_code pref_lang	SIM_FATAL_ERROR NUM_3 NUM_10 NUM_3 NUM_10 NOT_USED NOT_USED
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_NREG_IND	nreg_cs search_running new_forb_plmn limited_cause	NREG_NO_SERVICE SEARCH_NOT_RUNNING PLMN_NO_ID MMR_RC_NONE
History:	10.08.98	ACI Initial

4.2.7 BMIA206: Power On Sequence, Invalid SIM card, limited service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_NREG_IND	
	<=====	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc mmi_pro_file stk_pro_file	SIM_INITIALISATION NOT_USED NOT_USED
(2) SIM_ACTIVATE_CNF	error pin_cnt puk_cnt pin2_cnt puk2_cnt ec_code pref_lang	SIM_INVALID_CARD NUM_3 NUM_10 NUM_3 NUM_10 NOT_USED NOT_USED
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_NREG_IND	nreg_cs search_running new_forb_plmn limited_cause	NREG_LIMITED_SERVICE SEARCH_NOT_RUNNING PLMN_NO_ID MMR_RC_NONE
History:	10.08.98	ACI Initial

4.2.8 BMIA207: Power On Sequence, Invalid SIM card, no service

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	*=====> *	
(2)	SIM_ACTIVATE_CNF	
	*<===== *	
(3)	MMR_PLMN_MODE_REQ	
	*=====> *	
(4)	MMR_REG_REQ	
	*=====> *	
(5)	MMR_NREG_IND	
	*<===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc mmi_pro_file stk_pro_file	SIM_INITIALISATION NOT_USED NOT_USED
(2) SIM_ACTIVATE_CNF	error pin_cnt puk_cnt pin2_cnt puk2_cnt ec_code pref_lang	SIM_INVALID_CARD NUM_3 NUM_10 NUM_3 NUM_10 NOT_USED NOT_USED
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_NREG_IND	nreg_cs search_running new_forb_plmn limited_cause	NREG_NO_SERVICE SEARCH_NOT_RUNNING PLMN_NO_ID MMR_RC_NONE
History:	10.08.98	ACI Initial

4.2.9 BMIA208: Power On Sequence, Blocked SIM card

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	*=====> *	
(2)	SIM_ACTIVATE_CNF	
	*<===== *	
(3)	SIM_MMI_INSERT_IND	
	*<===== *	
(4)	SIM_READ_REQ	
	*=====> *	
(5)	SIM_READ_CNF	
	*<===== *	
(6)	SIM_READ_REQ	
	*=====> *	
(7)	SIM_READ_CNF	
	*<===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc mmi_pro_file stk_pro_file	SIM_INITIALISATION NOT_USED NOT_USED
(2) SIM_ACTIVATE_CNF	error pin_cnt puk_cnt pin2_cnt puk2_cnt ec_code pref_lang	SIM_INVALID_PUK_1 NUM_3 NUM_10 NUM_3 NUM_10 EC_CODES NOT_USED
(3) SIM_MMI_INSERT_IND	func sim_serv imsi_field pref_plmn phase access_acm access_acmmax access_puct	SIM_ADN_ENABLED F_SIM_SRV NOT_USED NOT_USED PHASE_2_SIM NOT_USED NOT_USED NOT_USED
(4) SIM_READ_REQ	source offset datafield length max_length	SRC_MMI NOT_USED SIM_CPHS_CINF NOT_PRESENT_8BIT NOT_USED
(5) SIM_READ_CNF	datafield error length trans_data	SIM_CPHS_CINF SIM_NO_ERROR NOT_USED NOT_USED
(6) SIM_READ_REQ	source	SRC_MMI

	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF		
	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED

History: 10.08.98 ACI Initial

4.2.10 BMIA210: Power On Sequence with PIN entering, initial testcase

Description:

Preamble: BMIA001

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=POWER)		
(1)	SIM_ACTIVATE_REQ	
	=====>	
(2)	SIM_ACTIVATE_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	
	<=====	

Parametrization:

Primitive	Parameter	Value
(1) SIM_ACTIVATE_REQ	proc	SIM_INITIALISATION
	mmi_pro_file	NOT_USED
	stk_pro_file	NOT_USED
(2) SIM_ACTIVATE_CNF	error	SIM_INVALID_PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
	ec_code	NOT_USED
	pref_lang	NOT_USED
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED

	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF		
	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF		
	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED

History: 10.08.98 ACI Initial

4.2.11 BMIA211: Power On Sequence with PIN entering, enter digits, success- full

Description:

Preamble: BMIA210
Variants: <A> .. <C>

APL	ACI	PS
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(3)	SIM_VERIFY_PIN_REQ	
	=====>	
(4)	SIM_VERIFY_PIN_CNF	
	<=====	
(5)	MMR_PLMN_MODE_REQ	
	=====>	
(6)	MMR_REG_REQ	
	=====>	
(7)	MMR_REG_CNF	
	<=====	
(8)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
<A>	plmn	PLMN_262_02
	plmn	PLMN_262_03
<C>		
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.12 BMIA212: Power On Sequence with PIN entering, enter digits and clear

Description:

Preamble: BMIA210

APL	ACI	PS
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_B
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO

History:

10.08.98

ACI Initial

4.2.13 BMIA213: Power On Sequence with PIN entering, enter digits and clear II

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source pin pin_id	SRC_MMI PIN_1_VALUE_C PIN_1
(2) SIM_VERIFY_PIN_CNF	error pin_id pin_cnt puk_cnt pin2_cnt puk2_cnt	SIM_NO_ERROR PIN_1 NUM_3 NUM_10 NUM_3 NUM_10
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01

(6) MMR_PLMN_MODE_REQ

mode

MODE_AUTO

History:

10.08.98

ACI Initial

4.2.14 BMIA214: Power On Sequence with PIN entering, clear if nothing to clear

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source pin pin_id	SRC_MMI PIN_1_VALUE_C PIN_1
(2) SIM_VERIFY_PIN_CNF	error pin_id pin_cnt	SIM_NO_ERROR PIN_1 NUM_3

	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.15 BMIA215: Power On Sequence with PIN entering, exact eight digits

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_D
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
(3) MMR_PLMN_MODE_REQ	puk2_cnt	NUM_10
	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01

(6) MMR_PLMN_MODE_REQ

mode

MODE_AUTO

History:

10.08.98

ACI Initial

4.2.16 BMIA216: Power On Sequence with PIN entering, exact eight digits with clearing

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=9)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_E
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
(3) MMR_PLMN_MODE_REQ	puk2_cnt	NUM_10
	mode	MODE_AUTO

(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.17 BMIA217: Power On Sequence with PIN entering, more then eight digits

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=RIGHT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=9)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=0)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=0)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

<u>Primitive</u>	<u>Parameter</u>	<u>Value</u>
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_E
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10

(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.18 BMIA218: Power On Sequence with PIN entering, okay after three digits

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(2)	SIM_VERIFY_PIN_CNF	
	*<===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_G
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_INVALID_PIN_1
	pin_id	PIN_1
	pin_cnt	NUM_2
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
History:	10.08.98	ACI Initial

4.2.19 BMIA219: Power On Sequence with PIN entering, wrong keys used

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=STAR)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
(3)	MMR_PLMN_MODE_REQ	
	=====>	
(4)	MMR_REG_REQ	
	=====>	
(5)	MMR_REG_CNF	
	<=====	
(6)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(4) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(5) MMR_REG_CNF	plmn	PLMN_262_01
(6) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.20 BMIA220: Power On Sequence with PIN entering, failure on verification

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	=====>	
(2)	SIM_VERIFY_PIN_CNF	
	<=====	
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(3)	SIM_VERIFY_PIN_REQ	
	=====>	
(4)	SIM_VERIFY_PIN_CNF	
	<=====	
(5)	MMR_PLMN_MODE_REQ	
	=====>	
(6)	MMR_REG_REQ	
	=====>	
(7)	MMR_REG_CNF	
	<=====	
(8)	MMR_PLMN_MODE_REQ	
	=====>	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_INVALID_PIN_1
	pin_id	PIN_1
	pin_cnt	NUM_2
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
(3) SIM_VERIFY_PIN_REQ	puk2_cnt	NUM_10
	source	SRC_MMI

	pin	PIN_1_VALUE
	pin_id	PIN_1
(4) SIM_VERIFY_PIN_CNF	error	SIM_NO_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(5) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(6) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(7) MMR_REG_CNF	plmn	PLMN_262_01
(8) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
History:	10.08.98	ACI Initial

4.2.21 BMIA221: Power On Sequence with PIN entering, general failure - test-case don't run

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(2)	SIM_VERIFY_PIN_CNF	
	*<===== *	
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(3)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(4)	SIM_VERIFY_PIN_CNF	
	*<===== *	
(5)	MMR_PLMN_MODE_REQ	
	*=====> *	
(6)	MMR_REG_REQ	
	*=====> *	
(7)	MMR_REG_CNF	
	*<===== *	
(8)	MMR_PLMN_MODE_REQ	
	*=====> *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_FATAL_ERROR
	pin_id	PIN_1
	pin_cnt	NUM_2
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10

(3) SIM_VERIFY_PIN_REQ	source pin pin_id	SRC_MMI PIN_1_VALUE PIN_1
(4) SIM_VERIFY_PIN_CNF	error pin_id pin_cnt puk_cnt pin2_cnt puk2_cnt	SIM_NO_ERROR PIN_1 NUM_3 NUM_10 NUM_3 NUM_10
(5) MMR_PLMN_MODE_REQ	mode	MODE_AUTO
(6) MMR_REG_REQ	service_mode	SERVICE_MODE_FULL
(7) MMR_REG_CNF	plmn	PLMN_262_01
(8) MMR_PLMN_MODE_REQ	mode	MODE_AUTO

History: 10.08.98 ACI Initial

4.2.22 BMIA222: Power On Sequence with PIN entering, repeated failures on verification

Description:

Preamble: BMIA210

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(2)	SIM_VERIFY_PIN_CNF	
	*<===== *	
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(3)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(4)	SIM_VERIFY_PIN_CNF	
	*<===== *	
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(5)	SIM_VERIFY_PIN_REQ	
	*=====> *	
(6)	SIM_VERIFY_PIN_CNF	
	*<===== *	
TIMEOUT_WAIT (5000)		

Parametrization:

Primitive	Parameter	Value
(1) SIM_VERIFY_PIN_REQ	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(2) SIM_VERIFY_PIN_CNF	error	SIM_INVALID_PIN_1
	pin_id	PIN_1
	pin_cnt	NUM_2
	puk_cnt	NUM_10

	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) SIM_VERIFY_PIN_REQ		
	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(4) SIM_VERIFY_PIN_CNF		
	error	SIM_INVALID_PIN_1
	pin_id	PIN_1
	pin_cnt	NUM_1
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(5) SIM_VERIFY_PIN_REQ		
	source	SRC_MMI
	pin	PIN_1_VALUE_F
	pin_id	PIN_1
(6) SIM_VERIFY_PIN_CNF		
	error	SIM_INVALID_PUK_1
	pin_id	PIN_1
	pin_cnt	NUM_0
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
History:	10.08.98	ACI Initial

4.2.23 BMIA223: Power On Sequence, PUK verification, successful case, without registration (missing in bmi_regi: SimManEH)

Description:

Preamble: BMIA222

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_UNBLOCK_REQ	
	*=====> *	
(2)	SIM_UNBLOCK_CNF	
	*<===== *	
(3)	SIM_MMI_INSERT_IND	
	*<===== *	
(4)	SIM_READ_REQ	
	*=====> *	
(5)	SIM_READ_CNF	
	*<===== *	
(6)	SIM_READ_REQ	
	*=====> *	
(7)	SIM_READ_CNF	
	*<===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_UNBLOCK_REQ	source	SRC_MMI
	unlock_key	PUK_1_VALUE
	pin	PIN_1_VALUE
	pin_id	PUK_1
(2) SIM_UNBLOCK_CNF	error	SIM_NO_ERROR
	pin_id	PUK_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED

History: 10.08.98 ACI Initial

4.2.24 BMIA224: Power On Sequence, PUK verification, new PIN is different, switch off

Description:

Preamble: BMIA222

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_SYNC_REQ	
	*=====> *	
(2)	SIM_SYNC_CNF	
	*<===== *	
(3)	MMR_NREG_REQ	
	*=====> *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_SYNC_REQ	synccs	SYNC_DEACTIVATE
(2) SIM_SYNC_CNF	param	NOT_USED
(3) MMR_NREG_REQ	cs	CS_POW_OFF
History:	10.08.98	ACI Initial

4.2.25 BMIA225: Power On Sequence, PUK verification, PUK is wrong

Description:

Preamble: BMIA222

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_UNBLOCK_REQ	
	*=====>	*
(2)	SIM_UNBLOCK_CNF	
	*<=====	*
TIMEOUT_WAIT (4000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		

```

COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)
TIMEOUT_WAIT (5000)
COMMAND (MMI CONFIG KEY_SEQUENCE=1)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=2)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=3)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=4)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)
TIMEOUT_WAIT (5000)
COMMAND (MMI CONFIG KEY_SEQUENCE=1)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=2)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=3)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=4)
TIMEOUT_WAIT (2000)
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)
(3) | | SIM_UNBLOCK_REQ |
| | *=====> *
(4) | | SIM_UNBLOCK_CNF |
| | *<===== *
(5) | | SIM_MMI_INSERT_IND |
| | *<===== *
(6) | | SIM_READ_REQ |
| | *=====> *
(7) | | SIM_READ_CNF |
| | *<===== *
(8) | | SIM_READ_REQ |
| | *=====> *
(9) | | SIM_READ_CNF |
| | *<===== *
| | |

```

Parametrization:

Primitive	Parameter	Value
(1) SIM_UNBLOCK_REQ	source	SRC_MMI
	unlock_key	PUK_1_VALUE
	pin	PIN_1_VALUE
	pin_id	PUK_1
(2) SIM_UNBLOCK_CNF	error	SIM_INVALID_PUK_1
	pin_id	PUK_1
	pin_cnt	NUM_0
	puk_cnt	NUM_9
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) SIM_UNBLOCK_REQ	source	SRC_MMI
	unlock_key	PUK_1_VALUE
	pin	PIN_1_VALUE
	pin_id	PUK_1
(4) SIM_UNBLOCK_CNF	error	SIM_NO_ERROR

	pin_id	PUK_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(5) SIM_MMI_INSERT_IND		
	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(6) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF		
	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(8) SIM_READ_REQ		
	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(9) SIM_READ_CNF		
	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
History:	10.08.98	ACI Initial

4.2.26 BMIA226: Power On Sequence, PUK verification, long pressed clear

Description:

Preamble: BMIA222

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_PRESS=RIGHT)		
TIMEOUT_WAIT (2200)		
COMMAND (MMI CONFIG KEY_RELEASE=RIGHT)		
TIMEOUT_WAIT (2200)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_UNBLOCK_REQ	
	*===== > *	
(2)	SIM_UNBLOCK_CNF	
	* <===== *	
(3)	SIM_MMI_INSERT_IND	

		* <=====	
(4)		SIM_READ_REQ	
		* =====>	
(5)		SIM_READ_CNF	
		* <=====	
(6)		SIM_READ_REQ	
		* =====>	
(7)		SIM_READ_CNF	
		* <=====	

Parametrization:

Primitive	Parameter	Value
(1) SIM_UNBLOCK_REQ	source	SRC_MMI
	unlock_key	PUK_1_VALUE
	pin	PIN_1_VALUE
	pin_id	PUK_1
(2) SIM_UNBLOCK_CNF	error	SIM_NO_ERROR
	pin_id	PUK_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF	datafield	SIM_ECC
	error	SIM_NO_ERROR

length
trans_data

NOT_USED
NOT_USED

History:

10.08.98

ACI Initial

4.2.27 BMIA227: Power On Sequence, PUK verification, new PIN, long pressed clear

Description:

Preamble: BMIA222

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=5)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=6)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=7)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=8)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (5000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_PRESS=RIGHT)		
TIMEOUT_WAIT (2200)		
COMMAND (MMI CONFIG KEY_RELEASE=RIGHT)		
TIMEOUT_WAIT (2200)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=3)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=4)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=LEFT)		
(1)	SIM_UNBLOCK_REQ	
	=====>	
(2)	SIM_UNBLOCK_CNF	
	<=====	
(3)	SIM_MMI_INSERT_IND	
	<=====	
(4)	SIM_READ_REQ	
	=====>	
(5)	SIM_READ_CNF	
	<=====	
(6)	SIM_READ_REQ	
	=====>	
(7)	SIM_READ_CNF	

	* <===== *	

Parametrization:

Primitive	Parameter	Value
(1) SIM_UNBLOCK_REQ	source	SRC_MMI
	unlock_key	PUK_1_VALUE
	pin	PIN_1_VALUE
	pin_id	PUK_1
(2) SIM_UNBLOCK_CNF	error	SIM_NO_ERROR
	pin_id	PUK_1
	pin_cnt	NUM_3
	puk_cnt	NUM_10
	pin2_cnt	NUM_3
	puk2_cnt	NUM_10
(3) SIM_MMI_INSERT_IND	func	SIM_ADN_ENABLED
	sim_serv	F_SIM_SRV
	imsi_field	NOT_USED
	pref_plmn	NOT_USED
	phase	PHASE_2_SIM
	access_acm	NOT_USED
	access_acmmax	NOT_USED
	access_puct	NOT_USED
(4) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_CPHS_CINF
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(5) SIM_READ_CNF	datafield	SIM_CPHS_CINF
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED
(6) SIM_READ_REQ	source	SRC_MMI
	offset	NOT_USED
	datafield	SIM_ECC
	length	NOT_PRESENT_8BIT
	max_length	NOT_USED
(7) SIM_READ_CNF	datafield	SIM_ECC
	error	SIM_NO_ERROR
	length	NOT_USED
	trans_data	NOT_USED

History: 10.08.98 ACI Initial

4.2.28 BMIA228: Power On Sequence, Invalid Sim Card, start Emergency call

Description:

Preamble: BMIA206

APL	ACI	PS
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=1)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=2)		
TIMEOUT_WAIT (2000)		
COMMAND (MMI CONFIG KEY_SEQUENCE=SEND)		
(1)	MNCC_SETUP_REQ	
	*=====> *	

Parametrization:

Primitive	Parameter	Value
(1) MNCC_SETUP_REQ		
	ti	TI_MO_0
	prio	PRIO_EMERG_CALL
	ri	NOT_USED
	bcpara	NOT_USED
	bcpara2	NOT_USED
	called_party	NOT_USED
	called_party_sub	NOT_USED
	clir_sup	NOT_USED
	fac_inf	NOT_USED

History:	10.08.98	ACI Initial
----------	----------	-------------

Appendices

A. Acronyms

DS-WCDMA	Direct Sequence/Spread Wideband Code Division Multiple Access
-----------------	---------------------------------------------------------------

B. Glossary

International Mobile Telecommunication 2000 (IMT-2000/ITU-2000)	Formerly referred to as FPLMTS (Future Public Land-Mobile Telephone System), this is the ITU's specification/family of standards for 3G. This initiative provides a global infrastructure through both satellite and terrestrial systems, for fixed and mobile phone users. The family of standards is a framework comprising a mix/blend of systems providing global roaming. <URL: http://www.imt-2000.org/ >
------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------