



Technical Documentation

AGC 1.x - API Definition

Document Number:	L1D_AS331-1
TI Department	European Wireless Terminal Chipset Business Unit
Version:	2.1
Status:	APPROVED
Date:	March 17, 2006

Important Notice

IMPORTANT NOTICE

Texas Instruments Incorporated and / or its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products, software and services at any time and to discontinue any product, software or service without notice. Customers should obtain the latest relevant information during product design and before placing orders and should verify that such information is current and complete.

All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment. TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI products, software and / or services. To minimize the risks associated with customer products and applications, customers should provide adequate design, testing and operating safeguards.

Any access to and / or use of TI software described in this document is subject to Customers entering into formal license agreements and payment of associated license fees. TI software may solely be used and / or copied subject to and strictly in accordance with all the terms of such license agreements.

Customer acknowledges and agrees that TI products and / or software may be based on or implements industry recognized standards and that certain third party may claim intellectual property rights therein. The supply of products and / or the licensing of software do not convey a license from TI to any third party intellectual property rights and TI expressly disclaims liability for infringement of third party intellectual property rights.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products, software or services are used.

Information published by TI regarding third-party products, software or services does not constitute a license from TI to use such products, software or services or a warranty, endorsement thereof or statement regarding their availability. Use of such information, products, software or services may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, for any purpose without the express written permission of TI.

Change History

Date of change	Changed by	Approved by	Approval date	Version	Notes
March 7, 2005	Thierry Le Gall			0.1	(1)
March 15, 2005	Thierry Le Gall	Sébastien Guiriec	Mar. 15, 2005	1.0	(2)
April 05, 2005	Thierry Le Gall		April 05, 2005	1.1	(3)
April 13, 2005	Thierry Le Gall	Sébastien Guiriec	April 13, 2005	2.0	(4)
July 25, 2005	Thierry Le Gall			2.1	(5)

Notes

- (1) Creation of the document.
- (2) Approval.
- (3) Minor correction in introduction. Updated (2.2).
- (4) Major correction: API content from 9 to 11 parameters.
- (5) Updated reference table.

Table of Contents

1	Introduction	5
2	AGC 1.x Module API	5
2.1	Entry Functions.....	5
2.1.1	Function f_agc_top ().....	5
2.1.2	Function f_agc_init ()	6
2.2	AGC 1.x Module Interface.....	6
	Appendices	9
A.	Appendix: AGC 1.x Parameters - Recommended Values	9

List of Figures and Tables

Table 2.1	The AGC 1.x Top Function Arguments.....	5
Table 2.2	The AGC 1.x Initialization Function Arguments	6
Table 2.3	The AGC 1.x API Parameters Description.....	6
Table 2.4	The AGC 1.x API Parameters Format and Range	7
Table 2.5	The AGC 1.x Parameters Recommended Values at 8kHz – 20ms.....	9
Table 2.6	The AGC 1.x Parameters Recommended Values at 8kHz – 10ms.....	9
Table 2.7	The AGC 1.x Parameters Recommended Values at 16kHz – 20ms.....	9
Table 2.8	The AGC 1.x Parameters Recommended Values at 16kHz – 10ms.....	10

Glossary

API	Application Protocol Interface
AGC	Automatic Gain Control
VAD	Voice Activity Detector

References

- [1] L1D_AS330 – AGC 1.x – Overview
- [2] [L1D_AS250 – VAD 1.x, 2.x – Overview](#)

1 Introduction

The purpose of this document is to describe the Application Protocol Interface (API) related to the Automatic Gain Control (AGC) [1]. This document applies for AGC 1.0 and next upgrades AGC 1.x. operating at 8kHz or 16kHz sampling frequencies (10ms or 20ms frame processing).

The AGC 1.x uses the Voice Activity Detector (VAD 2.x) as external module operating at 8kHz or 16kHz sampling frequencies (10ms or 20ms frame processing) [2].

First chapter describes the API of the AGC 1.x module. A. Appendix is dedicated to the recommended values of AGC 1.x parameters through API.

2 AGC 1.x Module API

This chapter describes the parameter interface of the AGC 1.x module.

2.1 Entry Functions

2.1.1 Function `f_agc_top ()`

Prototype:

```
void f_agc_top (T_AGC_STATIC_VAR *p_agc_data);
```

Description:

This AGC top level function contains the call of all signal processing functions necessary to perform the AGC algorithm. The function arguments are presented below (Table 2.1).

Arguments:

Type	Name	Flow	Description
T_AGC_STATIC_VAR	*p_agc_data	IN/OUT	Pointer on the AGC module static variables

Table 2.1 The AGC 1.x Top Function Arguments

The T_AGC_STATIC_VAR *p_agc_data structure pointer parameter is used to pass the static variables to the AGC top function as well as through the internal signal processing functions. In addition, the AGC configuration parameters are passed to the module through a data structure pointer T_AGC_PARAM *p_agc_param element of *p_agc_data. Those structures are detailed in the implementation document.

Requirements:

The entire signal processing functions code must be mapped on a single DSP page as it does not support extended addressing.

Reentrancy:

This API is reentrant.

Return value:

None.

2.1.2 Function f_agc_init ()

Prototype:

```
void f_agc_init (T_AGC_STATIC_VAR *p_agc_data);
```

Description:

This function is used to initialize the AGC module. The function arguments are presented below (Table 2.2)

Arguments:

Type	Name	Flow	Description
T_AGC_STATIC_VAR	*p_agc_data	IN/OUT	Pointer on the AGC module static variables

Table 2.2 The AGC 1.x Initialization Function Arguments

Requirements:

The init function code must be mapped on a single DSP page as it does not support extended addressing.

Reentrancy:

This API is reentrant.

Return value:

None.

2.2 AGC 1.x Module Interface

This chapter focuses on the API for AGC module. The API description, format of range of parameters is presented below (Table 2.3), (Table 2.4).

&	Type	Name	Description
+0	T_UINT16	d_agc_control	AGC enable/disable
+1	T_UINT16	d_agc_frame_size	AGC acquisition/restoration frame size
+2	T_SINT16	d_agc_targeted_level	AGC targeted level from dBm0 spec.
+3	T_SINT16	d_agc_signal_up	AGC gain up from dB spec.
+4	T_SINT16	d_agc_signal_down	AGC gain down from dB spec.
+5	T_SINT16	d_agc_max_scale	AGC maximum gain from dB spec.
+6	T_SINT16	d_agc_gain_smooth_alpha	AGC gain smoothing factor
+7	T_SINT16	d_agc_gain_smooth_alpha_fast	AGC gain fast smoothing factor
+8	T_SINT16	d_agc_gain_smooth_beta	AGC gain smoothing factor
+9	T_SINT16	d_agc_gain_smooth_beta_fast	AGC gain fast smoothing factor
+10	T_SINT16	d_agc_gain_intp_flag	AGC gain interpolation enable/disable

Table 2.3 The AGC 1.x API Parameters Description

&	Type	Format	Range	Comments
+0	T_UINT16	16b/Q0	[0x0000,	AGC disabled,
			0x0001,	AGC enabled 8kHz
			0x0002]	AGC enabled 16kHz
+1	T_SINT16	16b/Q0	[0x0050,	80 samples, 1X10ms frame processing (FP) at 8kHz
			0x00A0,	160 samples, 2X10ms FP (8kHz), 1X10ms FP (16kHz)
			0x0140]	320 samples, 2X10ms FP (16kHz)
+2	T_SINT16	16b/Q15	[0x0502...	minimal: -22dBm0 power
			0x09FE...	nominal: -16dBm0 power, see also note (1)
			0x13F0]	maximal: -10dBm0 power
+3	T_SINT16	16b/Q10	0x7E7E	nominal: +15dB power, see also note (2)
+4	T_SINT16	16b/Q15	0x7FB4	nominal Ref. -0.01dB, see also note (3)
+5	T_SINT16	16b/Q12	0x59F9	nominal Ref. +15dB, see also note (4)
+6	T_SINT16	16b/Q15	0x7EB8	nominal Ref. 0.99
+7	T_SINT16	16b/Q15	0x7333	nominal Ref. 0.9
+8	T_SINT16	16b/Q15	0x7F5C	nominal Ref. 0.095
+9	T_SINT16	16b/Q15	0x7333	nominal Ref. 0.9
+10	T_SINT16	16b/Q0	0x0000	nominal, interpolation disabled, see also note (5)
			0x0001	interpolation enabled, see also note (5)

Table 2.4 The AGC 1.x API Parameters Format and Range

- (1) The targeted level of the signal at AGC output could be computed from the specification of targeted level in dBm0 as follow:

$$d_agc_targeted_level = round \left\{ 2^{15} \cdot 10^{\frac{L_{target} - 6.15}{20}} \right\}, \quad (2.1)$$

where the targeted level is L_{target} . For example, $L_{target} = -16dBm0$ leads to $d_agc_targeted_level = 2558$ i.e. $d_agc_targeted_level = 0x09FE$.

- (2) The AGC gain increasing rate $d_agc_signal_up$ could be customized from specification of rate in dB as follow:

$$d_agc_signal_up = round \left\{ \frac{2^{15}}{2^5} \cdot 10^{\frac{\Gamma_{up}}{10}} \right\}, \quad (2.2)$$

where the increasing rate is Γ_{up} . For example, $\Gamma_{up} = 15dB$ leads to $d_agc_signal_up = 32382$ i.e. $d_agc_signal_up = 0x7E7E$.

- (3) The AGC gain decreasing rate $d_agc_signal_down$ could be customized from specification of rate in dB as follow:

$$d_agc_signal_down = round \left\{ 2^{15} \cdot 10^{\frac{\Gamma_{down}}{10}} \right\}, \quad (2.3)$$

where the increasing rate is Γ_{down} . For example, $\Gamma_{down} = -0.01dB$ leads to $d_agc_signal_down = 32692$ i.e. $d_agc_signal_down = 0x7FB4$.

- (4) The AGC maximal amplification $d_agc_max_scale$ could be customized from specification of amplification in dB as follow:

$$d_agc_max_scale = round \left\{ \frac{2^{15}}{2^3} \cdot 10^{\frac{g_{max}}{20}} \right\}, \quad (2.4)$$

where the maximum amplification is g_{max} . For example, $g_{max} = 15dB$ leads to $d_agc_max_scale = 23033$ i.e. $0x59F9$.

- (5) The AGC gain is interpolated from frame to frame on 32 samples (8000Hz) or 64 samples (16000Hz). The interpolation can be enable/disable using $d_agc_gain_intp_flag$. Nominal value is $d_agc_gain_intp_flag = 0$.

Appendices

A. Appendix: AGC 1.x Parameters - Recommended Values

&	Type	Name	Values	Reference
+0	T_UINT16	d_agc_control	0x0001	8kHz
+1	T_UINT16	d_agc_frame_size	0x00A0	160 samples
+2	T_SINT16	d_agc_targeted_level	0x09FE	-16dBm0
+3	T_SINT16	d_agc_signal_up	0x7E7E	15dB
+4	T_SINT16	d_agc_signal_down	0x7FB4	-0.01dB
+5	T_SINT16	d_agc_max_scale	0x59F9	15dB
+6	T_SINT16	d_agc_gain_smooth_alpha	0x7EB8	0.99
+7	T_SINT16	d_agc_gain_smooth_alpha_fast	0x7333	0.9
+8	T_SINT16	d_agc_gain_smooth_beta	0x7F5C	0.095
+9	T_SINT16	d_agc_gain_smooth_beta_fast	0x7333	0.9
+10	T_SINT16	d_agc_gain_intp_flag	0x0000	no interp.

Table 2.5 The AGC 1.x Parameters Recommended Values at 8kHz – 20ms

&	Type	Name	Values	Reference
+0	T_UINT16	d_agc_control	0x0001	8kHz
+1	T_UINT16	d_agc_frame_size	0x0050	80 samples
+2	T_SINT16	d_agc_targeted_level	0x09FE	-16dBm0
+3	T_SINT16	d_agc_signal_up	0x7E7E	15dB
+4	T_SINT16	d_agc_signal_down	0x7FB4	-0.01dB
+5	T_SINT16	d_agc_max_scale	0x59F9	15dB
+6	T_SINT16	d_agc_gain_smooth_alpha	0x7EB8	0.99
+7	T_SINT16	d_agc_gain_smooth_alpha_fast	0x7333	0.9
+8	T_SINT16	d_agc_gain_smooth_beta	0x7F5C	0.095
+9	T_SINT16	d_agc_gain_smooth_beta_fast	0x7333	0.9
+10	T_SINT16	d_agc_gain_intp_flag	0x0000	no interp.

Table 2.6 The AGC 1.x Parameters Recommended Values at 8kHz – 10ms

&	Type	Name	Values	Reference
+0	T_UINT16	d_agc_control	0x0002	16kHz
+1	T_UINT16	d_agc_frame_size	0x0140	320 samples
+2	T_SINT16	d_agc_targeted_level	0x09FE	-16dBm0
+3	T_SINT16	d_agc_signal_up	0x7E7E	15dB
+4	T_SINT16	d_agc_signal_down	0x7FB4	-0.01dB
+5	T_SINT16	d_agc_max_scale	0x59F9	15dB
+6	T_SINT16	d_agc_gain_smooth_alpha	0x7EB8	0.99
+7	T_SINT16	d_agc_gain_smooth_alpha_fast	0x7333	0.9
+8	T_SINT16	d_agc_gain_smooth_beta	0x7F5C	0.095
+9	T_SINT16	d_agc_gain_smooth_beta_fast	0x7333	0.9
+10	T_SINT16	d_agc_gain_intp_flag	0x0000	no interp.

Table 2.7 The AGC 1.x Parameters Recommended Values at 16kHz – 20ms

&	Type	Name	Values	Reference
+0	T_UINT16	d_agc_control	0x0002	16kHz
+1	T_UINT16	d_agc_frame_size	0x00A0	160 samples
+2	T_SINT16	d_agc_targeted_level	0x09FE	-16dBm0
+3	T_SINT16	d_agc_signal_up	0x7E7E	15dB
+4	T_SINT16	d_agc_signal_down	0x7FB4	-0.01dB
+5	T_SINT16	d_agc_max_scale	0x59F9	15dB
+6	T_SINT16	d_agc_gain_smooth_alpha	0x7EB8	0.99
+7	T_SINT16	d_agc_gain_smooth_alpha_fast	0x7333	0.9
+8	T_SINT16	d_agc_gain_smooth_beta	0x7F5C	0.095
+9	T_SINT16	d_agc_gain_smooth_beta_fast	0x7333	0.9
+10	T_SINT16	d_agc_gain_intp_flag	0x0000	no interp.

Table 2.8 The AGC 1.x Parameters Recommended Values at 16kHz – 10ms